



BS655-T22

- Platform concept with different function units
- Metal enclosure
- Wide range of alternative actuators
- Protection class IP66, IP67
- Switching point setting
- Symmetry thanks to toothed, centrally located shaft
- Central connection terminal

Data

Ordering data

EAN (European Article Number) 4030661533094

Approval - Standards

Certificates TÜV
cULus
CCC

General data

Standards	IEC 60947-5-1 EN 620
Enclosure material	Grey cast iron, painted
Material of the contacts, electrical	Silver
Material of the cover	Grey cast iron, painted
Gross weight	6,110 g

General data - Features

Number of auxiliary contacts 2

Number of safety contacts 2

Safety appraisal

Standards EN ISO 13849-1

Mission Time 20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC) 2,000,000 Operations

Mechanical data

Mechanical life, minimum 1,000,000 Operations

Positionierschritte für den Betätiger 10 °

Mechanical data - Connection technique

Cable entry 2 x M25 x 1.5

Cable section, minimum 0.5 mm², flexible

Cable section, maximum 2.5 mm², flexible

Ambient conditions

Degree of protection IP66 to EN 60529
IP67 to EN 60529

Ambient temperature, minimum -40 °C

Ambient temperature, maximum +70 °C

Protection rating I

Ambient conditions - Insulation value

Rated insulation voltage U_i	300 V
Rated impulse withstand voltage U_{imp}	4 kV
Degree of pollution to IEC/EN 60947-1	3

Electrical data

Thermal test current	6 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	3 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	3 A
Switching principle	Creep circuit element

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:29 AM