

A-K3P-M8-R-G-2,5M-GY-1-X-X-4

- Pre-wired cable
- 3-pole

Data

Ordering data

EAN (European Article Number)	4030661475622
eCl@ss number, Version 9.0	27-06-03-11
eCl@ss number, Version 11.0	27-06-03-11
ETIM number, version 6.0	EC001855
ETIM number, version 7.0	EC001855

General data

Standards	IEC 61076-2-104
Gross weight	71.3 g

General data - Features

Number of poles	3
Number of cable wires	3

Mechanical data - Connection technique

Length of cable	2.5 m
Wire cross-section	0.25 mm ²

Cable diameter	4.3 mm
Bending radius (fixed)	5 x Ø-cable
Bending radius (repeated)	10 x Ø-cable
Material of the Cable mantle	PVC

Mechanical data - connector side A

Connector typ	Female connector, M8
Design	straight
Connector coding	A
Connector latching	Latching interlocking
Material of the gland	Plastic, TPU
Material of the handle	Plastic, TPU
Colour of the handle	Black

Ambient conditions

Degree of protection	IP65 IP67 IP69
Ambient temperature, minimum (Connector)	-30 °C
Ambient temperature, maximum (Connector)	+90 °C
Temperature (fixed), minimum	-25 °C
Temperature (fixed), maximum	+80 °C
Temperature (repeated), minimum	+0 °C
Temperature (repeated), maximum	+80 °C

Electrical data

Rated operating voltage	60 V
Operating current	4,000 mA

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:30 AM