



AZ06KT

- Single-conductor entry with strain relief
- Thermoplastic enclosure
- Contact pin in actuator bridge
- 1 Actuating planes
- Protection against accidental contact with additional wall
- transparent cover
- fixing screws M4 undetachable, captive
- Fitting dimensions suitable for AZ 06x
- Self-cleaning through the frictional movement of the contact bridges
- Protection class IP20

Data

Ordering data

EAN (European Article Number)	4030661429755
eCl@ss number, Version 9.0	27-27-06-10
eCl@ss number, Version 11.0	27-27-06-10
ETIM number, version 6.0	EC002592
ETIM number, version 7.0	EC002592

General data

Standards	EN 81-20 EN 81-50
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver-plated Cu rivets
Material of the cover	transparent thermoplastic

Gross weight	35.2 g
--------------	--------

General data - Features

Suitable for elevators	Yes
Number of safety contacts	1

Mechanical data

Actuating panels	1
Mechanical life, minimum	1,000,000 Operations
Actuating stroke	7 mm
Actuating force, approx.	1.6 N
Mounting	Round holes

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable entry	Single-conductor entry with strain relief

Mechanical data - Dimensions

Width	72 mm
Height	22 mm
Depth	19 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature, minimum	-15 °C
Ambient temperature, maximum	+70 °C
Relative humidity, maximum	95 %
Note (Relative humidity)	non-condensing

Ambient conditions - Insulation value

Rated insulation voltage U_i	500 V
--------------------------------	-------

Electrical data

Thermal test current	4 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	2 A
Utilisation category DC-13	200 VDC
Utilisation category DC-13	2 A
Switching element	Opener (NC)
Switching principle	Self-cleaning pressure contact

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Notes

Note (General)	The connecting screws can be sealed with plugs. (2 plugs per switch)
----------------	--

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:24 AM