



V-SS4P-M12-S-G-1,5M-BK-2-X-A-4-69

Data

Ordering data

| | |
|-------------------------------|---------------|
| EAN (European Article Number) | 4030661512297 |
| eCl@ss number, Version 9.0 | 27-06-03-11 |
| eCl@ss number, Version 11.0 | 27-06-03-11 |
| ETIM number, version 6.0 | EC001855 |
| ETIM number, version 7.0 | EC001855 |

General data

| | |
|--------------|--------|
| Gross weight | 81.3 g |
|--------------|--------|

General data - Features

| | |
|-----------------------|---|
| Number of cable wires | 4 |
|-----------------------|---|

Mechanical data

| | |
|----------------------------|------|
| Tightening torque, maximum | 1 Nm |
|----------------------------|------|

Mechanical data - Connection technique

| | |
|----------------------------|----------------------|
| Length of cable | 1.5 m |
| Wire cross-section | 0.25 mm ² |
| Colour of the Cable mantle | Green |

Mechanical data - connector side A

| | |
|-----------------------|----------------------------|
| Connector typ | Male connector, M12 |
| Design | straight |
| Connector coding | A |
| Connector latching | Screw locking |
| Material of the gland | Metal, CuZn, nickel-plated |
| Colour of the handle | Black |

Mechanical data - connector side B

| | |
|-----------------------|----------------------------|
| Connector typ | Male connector, M12 |
| Design | straight |
| Connector coding | A |
| Connector latching | Screw locking |
| Material of the gland | Metal, CuZn, nickel-plated |
| Colour of the handle | Black |

Electrical data

| | |
|----------------------|-----|
| Thermal test current | 4 A |
|----------------------|-----|

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:50 AM