



## A-K3P-M12-S-W-2M-OG-1-1LP-A-2

- Pre-wired cable
- 3-pole

### Data

#### Ordering data

eCl@ss number, Version 9.0	27-44-01-02
eCl@ss number, Version 11.0	27-44-01-02
ETIM number, version 6.0	EC002062

#### General data

general information	A
Colour of the handle	Transparent
Gross weight	82 g

#### General data - Features

Integral System Diagnostics, status	Yes
Number of LEDs	1
Number of cable wires	3

#### Mechanical data - Connection technique

Length of cable	2 m
Wire cross-section	0.34 mm <sup>2</sup>
Material of the Cable mantle	PVC

## Mechanical data - connector side A

Connector typ	Female connector, M12
Design	angled
Material of the gland	Metal, CuZn, nickel-plated
Material of the handle	Plastic, TPU

## Ambient conditions

Degree of protection	IP67
----------------------	------

## Electrical data

Rated operating voltage	10 ... 30 VDC
Operating current	4,000 mA

## Status indication

Note (LED switching conditions display)	Circuit: p-type
---	-----------------

## Pin assignment

PIN 1	Brown
PIN 2	n.c.
PIN 3	Blue
PIN 4	Black

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:36 AM