



A-K4P-M8-S-G-2M-BK-2-X-X-4

- Pre-wired cable
- 4-pole

Data

Ordering data

EAN (European Article Number)	4030661476933
eCl@ss number, Version 9.0	27-06-03-11
eCl@ss number, Version 11.0	27-06-03-11
ETIM number, version 6.0	EC001855
ETIM number, version 7.0	EC001855

General data

Standards	IEC 61076-2-104
Gross weight	56.6 g

General data - Features

Halogen free	Yes (1)
Cable drag chain suitable	Yes (1)
Number of poles	4

Mechanical data

Tightening torque, maximum	0.6 Nm
----------------------------	--------

Mechanical data - Connection technique

Length of cable	2 m
Wire cross-section	0.25 mm ²
Cable diameter	4.3 mm
Bending radius (fixed)	5 x Ø-cable
Bending radius (repeated)	10 x Ø-cable
Colour of the Cable mantle	Black
Material of the Cable mantle	PUR

Mechanical data - connector side A

Connector typ	Female connector, M8
Design	straight
Connector latching	Screw locking
Material of the gland	Metal, CuZn, nickel-plated
Material of the handle	Plastic, TPU
Colour of the handle	Black

Mechanical data - Dimensions

Diameter of the ISO-thread	M8
----------------------------	----

Ambient conditions

Degree of protection	IP65 IP67 IP69
Ambient temperature, minimum (Connector)	-30 °C

Ambient temperature, maximum (Connector)	+90 °C
Temperature (fixed), minimum	-50 °C
Temperature (fixed), maximum	+90 °C
Temperature (repeated), minimum	-30 °C
Temperature (repeated), maximum	+90 °C

Electrical data

Thermal test current	4 A
Rated operating voltage	60 V
Operating current	4,000 mA

Pin assignment

PIN 1	Brown
PIN 2	White
PIN 3	Blue
PIN 4	Black

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:32 AM