



EX-BNS 250-11Z-3G/D

- Explosion protection for ATEX Zones 2 and 22
- Thermoplastic enclosure
- 33 mm x 25 mm x 13 mm
- Small body
- Concealed mounting possible
- Insensitive to transverse misalignment
- no mechanical wear
- For intrinsically safe current circuits (Ex i) to Ex-Zone 0 and 20

Data

Ordering data

EAN (European Article Number)	4030661332598
eCl@ss number, Version 9.0	27-27-24-02
eCl@ss number, Version 11.0	27-27-24-02
ETIM number, version 6.0	EC002544
ETIM number, version 7.0	EC002544

Explosion protection

Explosion protection: regulations	EN 13463-1 EN 13463-5 EN 60079-0 EN 60079-15 EN 60079-31 IEC 60947-5-3
Explosion protection zones	22 2

Explosion protection category	3D 3G
Explosion protection designation	<div> <div> <div>Ex</div> <div>II 3G Ex nC IIC T6 Gc X</div> </div> <div> <div>Ex</div> <div>II 3D Ex tc IIIC T80°C Dc X</div> </div> </div>
Manufacturer declaration	ATEX Zone 2 and 22

General data

Housing construction form	Block
Installation conditions (mechanical)	not flush
Enclosure material	Glass-fibre, reinforced thermoplastic
Gross weight	43 g

General data - Features

Coding	Yes
Short circuit detection	Yes
Short-circuit recognition	Yes
Prerequisite evaluation unit	Yes
Number of openers	1
Number of shutters	1

Safety appraisal

Standards	EN ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d- Value Normally-closed contact/Normally open contact (NC/NO)	25,000,000 Operations
---	-----------------------

Mechanical data

Active area	front side
Actuating element	Magnet
Impact energy, maximum	1 J
Direction of motion	Head-on to the active surface

Mechanical data - Switching distances according IEC 60947-5-3

Ensured switch distance "ON" S_{ao}	4 mm
Ensured switch distance "OFF" S_{ar}	14 mm

Mechanical data - Connection technique

Terminal Connector	Cable
Length of cable	1 m
Wire cross-section	0.25 mm ²
Wire cross-section	23 AWG
Material of the Cable mantle	PVC

Mechanical data - Dimensions

Length of sensor	13 mm
Width of sensor	33 mm
Height of sensor	25 mm

Ambient conditions

Degree of protection	IP67
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+70 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+70 °C
Resistance to vibrations to EN 60068-2-6	10 ... 55 Hz, amplitude 1 mm

Resistance to shock

30 g / 11 ms

Electrical data

Voltage type	DC (direct current)
Switching voltage, maximum	24 VDC
Switching current, maximum	0.1 A
Switching capacity, maximum	1 W
Switching frequency, maximum	5 Hz

Electrical data - Digital Output

Versions	Miscellaneous, Reed contacts
----------	------------------------------

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Accessory

Recommendation (actuator)	EX-BPS 250-3G/D
Recommended safety switchgear	SRB-E-301ST SRB-E-201LC

Notes

Note (General)	Contact symbols shown for the closed condition of the guard device. The contact configuration for versions with or without LED is identical.
----------------	---

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:49 AM