

## A-K3P-M8-S-W-2M-GY-1-2LP-X-4

- Pre-wired cable
- 3-pole

### Data

#### Ordering data

EAN (European Article Number)	4030661475639
eCl@ss number, Version 9.0	27-06-03-11
eCl@ss number, Version 11.0	27-06-03-11
ETIM number, version 6.0	EC001855
ETIM number, version 7.0	EC001855

#### General data

Standards	IEC 61076-2-101
Gross weight	61 g

#### General data - Features

Number of poles	3
Number of cable wires	3

#### Mechanical data - Connection technique

Length of cable	2 m
Wire cross-section	0.25 mm <sup>2</sup>

Cable diameter	4.3 mm
Bending radius (fixed)	5 x Ø-cable
Bending radius (repeated)	10 x Ø-cable
Material of the Cable mantle	PVC

## Mechanical data - connector side A

Connector typ	Female connector, M8
Design	angled with status LED
Connector coding	A
Connector latching	Screw locking
Material of the gland	Metal, CuZn, nickel-plated
Material of the handle	Plastic, TPU
Colour of the handle	Transparent

## Ambient conditions

Degree of protection	IP65 IP67 IP69
Ambient temperature, minimum (Connector)	-30 °C
Ambient temperature, maximum (Connector)	+90 °C
Temperature (fixed), minimum	-25 °C
Temperature (fixed), maximum	+80 °C
Temperature (repeated), minimum	+0 °C
Temperature (repeated), maximum	+80 °C

## Electrical data

Rated operating voltage	30 V
Operating current	4,000 mA

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:30 AM