



## SLC 410-E/R0910-20-BM

- **NOTICE: Not available! (Replacement: SLC 420)**
- Control Category 4

## Data

### Ordering data

Note (Delivery capacity)	Not available!
eCl@ss number, Version 9.0	27-27-27-04
eCl@ss number, Version 11.0	27-27-27-04

### General data

Standards	IEC/EN 61496-1/-2
Master- or Slave-function	master
Enclosure material	Aluminium
Reaction time, maximum	22.5 ms

### General data - Features

Cascadable	Yes
Beam coding available	Yes
Hide function	Yes
Integral System Diagnostics, status	Yes

Integral System Diagnostics	Yes
Number of beams	90
Number of fail-safe digital outputs	2

## Safety appraisal

Safety type in accordance with IEC 61496-1	4
--	---

## Mechanical data

Detection ability for test bodies at $v = 1.6 \text{ m/s}$	20 mm
Height of the protection field	910 mm
Range, protection field, minimum	0 mm
Range, protection field, maximum	18,000 mm
Wave length of the sensor	950 nm

## Mechanical data - Connection technique

Terminal Connector	Connector
Terminal connector, Recipient	Connector plug M12, 8-pole
Terminal, Connector, Transmitter	Connector plug M12, 5-pole
Length of the connectable cable, maximum	100 m

## Mechanical data - Dimensions

Length of sensor	35 mm
Width of sensor	45 mm
Height of sensor	1,011 mm

## Ambient conditions

Degree of protection	IP65 to EN 60529
Ambient temperature, minimum	+0 °C

Ambient temperature, maximum	+55 °C
Storage and transport temperature, minimum	-20 °C
Storage and transport temperature, maximum	+70 °C
Protection rating	III

## Electrical data

Voltage type	DC (direct current)
Switching voltage OSSD, HIGH signal	24 V
Electrical power consumption of the receiver	3 W
Electrical power consumption of the transmitter	2 W
Cable length (Master/Slave), maximum	50 m

## Electrical data - Fail-safe digital outputs

Output current, (fail-safe output), maximum	0.5 A
Versions	p-type

## Scope of delivery

Included in delivery	Emitter + receiver, mounting angle, T-slot nuts
----------------------	---

## Accessory

Recommended safety switchgear	SCR 402R-301
-------------------------------	--------------

## Notes

Note (General)	The SLC 410 BM Master can be combined with all slaves of the SLC 410...RFS series.
----------------	--

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 11:06 AM