



## ASMM-2M-PB-RRSS

- 2 AS interface master integrated
- Field bus gateway: PROFIBUS DP
- Integrated safety monitor for 2 AS-i circuits, 256 Devices
- 2 AS-i power supply unit decoupling with 2 x 4 A integrated; 1 power supply unit for 2 AS-i circuits possible
- Diagnostic interface: Ethernet RJ-45; safe cross-communication with multiple devices enabled; Web-Server integrated
- Controls up to 32 enabling circuits,
  - 2 enabling contacts with relay contacts 30 V / 3 A AC/DC integrated
  - 2 enabling contacts with integrated semi-conductor outputs 30 V / 0,5 A DC

## Data

### Ordering data

Note (Delivery capacity)	Not available!
EAN (European Article Number)	4030661425498
eCl@ss number, Version 9.0	27-37-18-19
eCl@ss number, Version 11.0	27-37-18-19
ETIM number, version 6.0	EC001449

### Approval - Standards

Certificates	cULus
--------------	-------

### General data

Enclosure material

Metal film

Gross weight

972.8 g

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:14 AM