# **DATASHEET**





# TK 452-02Y

- Metal enclosure
- 118 mm x 127 mm x 64 mm (basic component)
- Actuator heads can be repositioned by 4 x 90°
- 2 cable entries M 20 x 1.5

### **Data**

### **Ordering data**

eCl@ss number, Version 9.0 27-27-06-01

eCl@ss number, Version 11.0 27-27-06-01

ETIM number, version 6.0 EC000030

ETIM number, version 7.0 EC000030

### **General data**

Standards EN 60947-5-1

Active principle mechanical

Slide form Castor

Enclosure material Grey cast iron, galvanised

Enclosure coating material painted

Material of the contacts, electrical Silver

Roller material Plastic

Gross weight 1,710 g

### **General data - Features**

Number of openers 2

### **Mechanical data**

Actuating element Offset roller lever

Mechanical life, minimum 10,000,000 Operations

Actuating angle, from left of switch

axis

45°

Actuating angle, from right of switch

axis

30°

Contact opening 2 x 6 mm

Actuating speed, minimum 1 mm/min

Actuating speed, maximum 0.5 m/s

Note (Actuating speed) Actuating speed with vertical actuating angle to switch axis

## Mechanical data - Connection technique

Terminal Connector Screw connection

Cable section, minimum 1.5 mm<sup>2</sup>

Cable section, maximum 2.5 mm<sup>2</sup>

Note (Cable section) All indications about the cable section are including the conductor ferrules.

Wire cross-section 13 AWG

### **Mechanical data - Dimensions**

Length of sensor 64 mm

Width of sensor 118 mm

Height of sensor 201 mm

Width of Castor 6.5 mm

Diameter of Castor 25 mm

### **Ambient conditions**

Degree of protection IP65 to EN 60529

Ambient temperature, minimum -30 °C

Ambient temperature, maximum +90 °C

### **Ambient conditions - Insulation value**

Rated insulation voltage U; 400 V

Rated impulse withstand voltage  $U_{imp}$  6 kV

### **Electrical data**

Thermal test current 16 A

Utilisation category AC-15 400 VAC

Utilisation category AC-15 4 A

Switching element Opener (NC)

Note (Switching element) with double break

Switching principle Creep circuit element

#### **Notes**

Note (General) Actuation from the right should be avoided, since this reduces the

mechanical life of the position switch.

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:23 AM