



A-K4P-M8-S-W-10M-BK-1-X-X-1

- Pre-wired cable
- 4-pole

Data

Ordering data

Note (Delivery capacity)	Phased-out product
EAN (European Article Number)	4030661385228
eCl@ss number, Version 9.0	27-44-01-02
eCl@ss number, Version 11.0	27-44-01-02
ETIM number, version 6.0	EC002062

General data

Standards	IEC 61076-2-104
Versions	angled
Gross weight	339.5 g

General data - Features

Number of poles	4
Number of cable wires	4

Mechanical data

Tightening torque, maximum	0.6 Nm
----------------------------	--------

Mechanical data - Connection technique

Length of cable	10 m
Wire cross-section	0.25 mm ²
Cable diameter	4.3 mm
Bending radius (fixed)	5 x Ø-cable
Bending radius (repeated)	10 x Ø-cable
Colour of the Cable mantle	Black
Material of the Cable mantle	PVC

Mechanical data - connector side A

Connector typ	Female connector, M8
Design	angled
Connector latching	Screw locking
Material of the gland	Metal, CuZn, nickel-plated
Material of the handle	Plastic, TPU
Colour of the handle	Black

Ambient conditions

Degree of protection	IP65 IP67 IP68 IP69
Ambient temperature, minimum (Connector)	-30 °C
Ambient temperature, maximum (Connector)	+90 °C
Temperature (fixed), minimum	-25 °C
Temperature (fixed), maximum	+80 °C

Temperature (repeated), minimum	+0 °C
Temperature (repeated), maximum	+80 °C

Electrical data

Thermal test current	4 A
Rated operating voltage	30 V
Operating current	4,000 mA

Pin assignment

PIN 1	Brown
PIN 2	White
PIN 3	Blue
PIN 4	Black

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:47 AM