

MST 1-PHASE CONTROL AND ISOLATION TRANSFORMER


P: 320VA IN: 208...550VAC OUT: 2x115VAC


Single-phase - Control and Isolation Transformers 320 VA Isolation class T 40/B Other voltages on request.

Link to Product

Illustration







Product may differ from Image



General data

Standards	EN 61558-1, EN 61558-2-4, EN 62041 category 0
Mounting method	Key-hole mounting
Temperature range	-20+40 °C (storage temperature -20+80 °C)
Test isolation voltage	4 kV (prim./sec.)
Drill hole Ø	5.8×10 mm
Fixing centers a×b×c	87×104 mm

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com



Dimensions H×W×D	115×135×132 mm
Output	
Output voltage	1× 230, 1× 115, 2× 115 V AC
Output rating	320 VA
Input	
Input voltage	208, 230, 380, 400, 420, 440, 460, 480, 500, 525, 550 V AC
Inrush current	32 A (208 V AC); 12 A (550 V AC)
Short-circuit current	32 A (208 V AC); 12 A (550 V AC)
Input current	1.73 A (208 V AC); 0.65 A (550 V AC)
Frequency	5060 Hz

Product article number of manufacturer 86146

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com