

MST 1-PHASE CONTROL AND ISOLATION TRANSFORMER


P: 1000VA IN: 230/400VAC OUT: 230VAC


Single-phase - Control and Isolation Transformers 1000 VA Spring clamp terminals Isolation class T 40/B Other voltages on request.

Link to Product

Illustration







Product may differ from Image



General data	
Standards	EN 61558-1, EN 61558-2-4, EN 62041 category 0
Mounting method	Key-hole mounting
Temperature range	-20+40 °C (storage temperature -40+80 °C)
Test isolation voltage	4 kV (prim./sec.)
Drill hole Ø	7×11 mm

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13



Fixing centers axbxc	102×135×7 mm
Dimensions H×W×D	128×174×160 mm
Output	
Output voltage	230 V AC
Output rating	1000 VA
Input	
Input voltage	230/400 V AC
Inrush current	66 A (230 V AC); 38 A (400 V AC)
Short-circuit current	148 A (230 V AC); 85 A (400 V AC)
Input current	4.73 A (230 V AC); 2.72 A (400 V AC)
Frequency	5060 Hz
Product article number of manufacturer	6686311