

MET 1-PHASE CONTROL AND ISOLATION TRANSFORMER

P: 1500VA IN: 400VAC+/- 5% OUT: 230VAC

Single-phase - Control and Isolation Transformers  
1500 VA  
Spring clamp terminals  
Isolation class T 60/B

Link to Product

Illustration



Product may differ from Image



| General data         |                                                 |
|----------------------|-------------------------------------------------|
| Standards            | EN 61558-1, EN 61558-2-4, EN 62041 category 0   |
| Mounting method      | Key-hole mounting                               |
| Temperature range    | -20...+60 °C (storage temperature -40...+80 °C) |
| Drill hole Ø         | 7×11 mm                                         |
| Fixing centers a×b×c | 141.5×135×7 mm                                  |
| Dimensions H×W×D     | 168×174×162 mm                                  |

| Output                                 |                    |
|----------------------------------------|--------------------|
| Output voltage                         | 230 V AC           |
| Output rating                          | 1500 VA            |
| Input                                  |                    |
| Input voltage                          | 400 V AC $\pm 5\%$ |
| Inrush current                         | 50 A (400 V AC)    |
| Short-circuit current                  | 201.5 A (400 V AC) |
| Input current                          | 3.97 A (400 V AC)  |
| Frequency                              | 50...60 Hz         |
| Product article number of manufacturer |                    |
| 6686061                                |                    |