



MTS 1-PHASE SAFETY TRANSFORMER

P: 100VA IN: 230/400VAC +/- 15VAC OUT: 24VAC

Single-phase safety transformer
100 VA
Spring clamp terminals
Isolation class T 40/B
Other voltages on request.

[Link to Product](#)

Illustration



Product may differ from Image



General data	
Standards	EN 61558-1, EN 61558-2-6, EN 62041 category 0
Mounting method	Long-hole mounting or DIN-rail mountable TH35 (EN 60715)
Temperature range	-20...+40 °C (storage temperature -40...+80 °C)
Test isolation voltage	4 kV (prim./sec.)
Drill hole Ø	4.8x8.4 mm

Fixing centers a×b×c	64.5×64×4.8 mm
----------------------	----------------

Dimensions H×W×D	86×84×98 mm
------------------	-------------

Output

Output voltage	24 V AC (SELV)
----------------	----------------

Output rating	100 VA
---------------	--------

Input

Input voltage	230/400 ±15 V AC
---------------	------------------

Inrush current	4.1 A (230 V AC); 2.3 A (400 V AC)
----------------	------------------------------------

Short-circuit current	6.6 A (230 V AC); 3.8 A (400 V AC)
-----------------------	------------------------------------

Input current	0.5 A (230 V AC); 0.3 A (400 V AC)
---------------	------------------------------------

Frequency	50...60 Hz
-----------	------------

Product article number of manufacturer	6686362
--	---------