

## Emparro Power Supply 3-PHASE

IN: 360 - 500VAC OUT: 24-28V/5ADC

INPUT: 3× 324...572 V AC / 450...745 V DC

OUTPUT: 24...28 V DC

Current: 5 A


Varnished board

### Link to Product

#### Illustration



Product may differ from Image



#### General data

Standards	IEC 61010-2-201, EN 61204-3, EN 55011 B, EN 61000-3-2, SEMI F47
Mounting method	DIN-rail mountable TH35 (EN 60715)
Temperature range	-40...+70 °C, ...+70 °C derating (storage temperature -40...+85 °C)
Relative humidity	5...95%, no condensation
Protection	IP20
Efficiency	92.5% (3× 400 V AC); 91.8% (3× 480 V AC)
Connection	Push-In spring clamp terminals
Dimensions H×W×D	143×50×143 mm

#### Output

Output voltage	24 V DC (SELV), ±1%; 24...28 V adjustable
Power Boost	I <sub>out</sub> N × 150% (min. 5 s)
LED display	LED (green): OK; LED (red): overload, overheating or short-circuit
Output current	3.7 A (70 °C); 5.0 A (60 °C); 6.0 A (45 °C)
Mains failure bridging time	min. 25 ms (3× 360 V AC); 5 A (24 V DC)
Ripple	max. 20 mV eff/rms
Spikes	max. 50 mV ss/pp
Unit protection	short-circuit and overload protected, permanently by 20% (to 45 °C)
Parallel usage/serial usage	max. 3 units

#### Input

Input voltage	3× 324...572 V AC/450...745 V DC
---------------	----------------------------------

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com

Input current	0.45 A (3× 360 V AC); 0.3 A (3×500 V AC)
Inrush current after 1 ms	max. 9.5 A (3× 500 V AC)
Power factor	0.61 (3× 400 V AC)
Frequency	50...60 Hz
Input fuse (internal)	3× 6.3 A (T)
Product article number of manufacturer	87690