

MOTOR SUPPRESSOR


Varistor, 3x400VAC/4kW


3× 400 V AC VDR isolated M6 PG9 Suppressors for other voltages, frequencies, and motor ratings available on request. Do not use RC motor suppressors with frequency inverters.

Link to Product









Product may differ from Image



Technical Data

Technical Data	
Frequency	10400 Hz
Input voltage	400400 V AC
Material	Flame retardant plastic acc. to (UL 94)
Ring terminals	isolated M6

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com



Potting compound	2-component epoxy
General data	
Mounting method	on motor terminal box with plug connector
Temperature range	-20+60 °C
Connection	approx. 100 mm, single cores 0.5 mm ²
Dimensions H×W×D	25×25×40 mm

Product article number of manufacturer 23110

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com