

RMME 11/110 AC INPUT RELAY



IN: 110 VAC/DC - OUT: 250 VAC/DC / 1 A

1 relay; 1 NO contact

6 A

110 V AC

Screw terminals

[Link to Product](#)**Illustration**

Product may differ from Image

General data

Mounting method	DIN-rail mountable TH35 or G32 (EN 60715)
Temperature range	-20...+60 °C
Test isolation voltage	1.5 kV
Mech./ elect. life	100 000 000 switching cycles/load dependent
Dimensions HxWxD	56x12x65 mm

Output

Min. load current	1 mA
Contact material	AG Ni hv
Energize/release/contact bounce time	10/10/1 ms
Switching voltage	max. 250 V AC/DC

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com

Switching frequency	max. 15 Hz
Power rating (voltage dependent)	max. 1500 VA/120 W
Switching current per output	max. 6 A
Input	
Connection voltage - current	110 V AC/DC (95...121 V AC/DC) - 3.5 mA
LED display	LED (yellow)
Utilization category	
AC-15	4 A (24/110/230 V AC)
AC-1	6 A (24/110/230 V AC)
DC-13	2 A (24 V DC); 0.25 A (110 V DC); 0.1 A (230 V DC)
Product article number of manufacturer	51526