

RM-21/230V AC OUTPUT RELAY



IN: 230 VAC/DC - OUT: 250 VAC/DC / 5 A

2 relays; each 1 NO/NC contact

8 A

230 V AC

Screw terminals

[Link to Product](#)**Illustration**

Product may differ from Image

General data

Mounting method	DIN-rail mountable TH35 or G32 (EN 60715)
Temperature range	-20...+50 °C
Test isolation voltage	4.0 kV
Mech./ elect. life	20 000 000 switching cycles/load dependent
Dimensions HxWxD	75x22.5x102 mm

Output

Min. load current	100 mA
Contact material	Ag Sn O ₂
Energize/release/contact bounce time	10/10/2 ms
Switching voltage	max. 250 V AC/DC

Switching frequency	max. 0.1 Hz (with load)
Power rating (voltage dependent)	max. 1250 VA/240 W
Switching current per output	max. 8 A
Input	
Connection voltage - current	230 V AC (195...250 V AC) - 10 mA
LED display	LED (red)
Utilization category	
AC-15	3 A (24/110/230 V AC)
AC-1	8 A (24/110/230 V AC)
DC-13	1.5 A (24 V DC); 0.3 A (110 V DC); 0.15 A (230 V DC)
Product article number of manufacturer	51412