

**MIRO 6.2 OUTPUT RELAY WITH TOGGLE SWITCH**

IN: 24 VAC/DC - OUT: 250 VAC/DC / 6 A

1 NO contact




6 A


24 V AC/DC

with protected H-O-A toggle switch

Screw terminals

LED (red/green)

[Link to Product](#)**Illustration**



Product may differ from Image

#### General data

Mounting method	DIN-rail mountable (EN 60715)
Temperature range	-20...+55 °C
Test isolation voltage	4 kV; safe separation (EN 60947-1)
Mech./ elect. life	20 000 000 switching cycles/load dependent
Dimensions H×W×D	91×6.2×71 mm

#### Output

Min. load current	100 mA (12 V DC)
Contact material	Ag Sn O <sub>2</sub>
Energize/release/contact bounce time	8/20/2 ms
Switching voltage	max. 250 V AC/DC
Switching frequency	max. 10 Hz
Power rating (voltage dependent)	max. 1500 VA/120 W
Switching current per output	max. 6 A

#### Input

Connection voltage - current	24 V AC/DC (19.2...28 V AC/DC) - 7 mA
LED display	LED (green): auto mode; LED (red): manual mode

#### Utilization category

AC-15	3 A (24/110/230 V AC)
AC-12	6 A (24/110/230 V AC)
DC-13	1 A (24 V DC); 0.2 A (110 V DC); 0.1 A (230 V DC)

Product article number of manufacturer	526010
--	--------