



RM 14/230V AC OUTPUT RELAY

IN: 230 VAC/DC - OUT: 250 VAC/DC / 2 A

1 relay; 4 NO/NC contacts
2 A
230 V AC
Screw terminals

[Link to Product](#)**Illustration**

Product may differ from Image

General data

Mounting method	DIN-rail mountable TH35 or G32 (EN 60715)
Temperature range	-20...+50 °C
Test isolation voltage	1.5 kV
Mech./ elect. life	50 000 000 switching cycles/load dependent
Dimensions HxWxD	75x22.5x102 mm

Output

Min. load current	0.1 mA
Contact material	Ag Au
Energize/release/contact bounce time	10/20/2 ms
Switching voltage	max. 250 V AC/DC

Switching frequency	max. 0.1 Hz (with load)
---------------------	-------------------------

Power rating (voltage dependent)	max. 125 VA/60 W
----------------------------------	------------------

Switching current per output	max. 2 A
------------------------------	----------

Input

Connection voltage - current	230 V AC (195...250 V AC) - 10 mA
------------------------------	-----------------------------------

LED display	LED (red)
-------------	-----------

Utilization category

AC-15	1 A (24 V AC); 0.1 A (230 V AC)
-------	---------------------------------

AC-12	2 A (24 V AC); 0.5 A (230 V AC)
-------	---------------------------------

DC-13	0.8 A (24 V DC); 0.01 A (230 V DC)
-------	------------------------------------

Product article number of manufacturer	51413
--	-------