

Xenterra 5TX unmanaged Switch 5 Port 100Mbit

5 port unmanaged switch DIN-rail mountable TH35 (EN 60715) Connection cables are in the online shop under "Connection Technology".

Link to Product

Illustration





Product may differ from Image



Technical Data	
Operating voltage	828 V AC/936 V DC
Transfer rate	10/100 Mbit/s full duplex
Operating modes	Autocrossing Autonegotiation
General data	
Mounting method	DIN-rail mountable TH35 (EN 60715)
Temperature range	-40+70 °C (storage temperature -40+85 °C)
Housing	Metal black
Protection	IP20
Dimensions H×W×D	105×42×32.5 mm
Connections	
Fieldbus	5× RJ45
Supply	Push-In spring clamp terminals, 0.22.5 mm ² (0.251.5 mm ²)
Switch Management	
Protocols	no
Port Mirroring	no
VLAN (QoS) IEEE 802.p	yes
Alarm contact	no
Remote maintenance	no
Webserver	no
Switch Form	Unmanaged Switch
Product article number of manufacturer	58900
Diagnostic	

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13



Communication status via LED

yes

Monitoring - no voltage