



MIRO TR 24VDC FK OPTO-COUPLED MODULE

IN: 53 VDC - OUT: 48 VDC / 0,5 A - 1 C/O contact

 Transistor 0.5 A
 24 V DC
 electr. NO/NC contact
 Spring clamp terminals

[Link to Product](#)
Illustration


Product may differ from Image


General data

Mounting method	DIN-rail mountable (EN 60715)
Temperature range	-20...+60 °C
Test isolation voltage	3.75 kV
Housing	Black plastic, flame retardant
Dimensions H×W×D	91×6.2×70 mm

Output

The information in this brochure has been compiled with the utmost care.

Liability for the correctness, completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com

Leakage current (output is open)	max. 0.1 mA
Switching time ON/OFF	40/150 µs
Saturation voltage (across output)	max. 1.2 V DC
Switching voltage	5...48 V DC
Switching frequency	max. 10 Hz
Switching current per output	0.1 mA...0.5 A

Input	
Control current	6 mA
Voltage range OFF	0...5 V DC
Voltage range ON	10...53 V DC
LED display	LED (yellow)

Product article number of manufacturer	6652510
--	---------