

MODLINK MSDD DATA INSERT

1×SUB-D9 female/female + 1×RJ45 + 1×RJ12

RJ45; RJ12; SUB-D9

1× RJ45, 8-pole metal, CAT5e (female/female)
 1× RJ12 (6-pole plastic)
 1× SUB-D9 (female/female)

[Link to Product](#)

Illustration



Product may differ from Image



General data

Dimensions H×W×D 88×51×45 mm

RJ45

Operating current (UL Rating) max. 175 mA

Locking of ports Snap In

Connection front side RJ45

Connection rear side RJ45

Operating voltage (UL Rating) max. 30 V AC/42.4 V DC

Specification CAT5e, Class D, 100 MHz, (EN 50173-1)

SUB-D9

Connection rear side SUB-D (female)

Operating current (UL Rating) max. 175 mA

Connection front side SUB-D (female)

Locking of ports UNC 4...40 bolt

Operating voltage (UL Rating) max. 30 V AC/42.4 V DC

Operating current 3 A

No. of poles 9-pole

Operating voltage 48 V AC/DC

RJ12

Operating voltage max. 48 V AC/DC

Connection front side	RJ12
Connection rear side	RJ12
Locking of ports	Snap In
Operating current	max. 1 A
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Operating current (UL Rating)	max. 175 mA
Shielding plate	
Tightening torque	0.9 Nm ± 0.1
Connection	Threaded hole M4
Product article number of manufacturer	4000-68000-1120000