

MODLINK MSDD SINGLE COMBI INSERT USA NEMA 1-15

1xSUD-D25 female/male + 1xRJ45 female/female

 1x NEMA 1-15 (plug-solder connection)
 1x RJ45, 8-pole metal, CAT5e (female/female)
 1x SUB-D25 (female/male)

[Link to Product](#)
Illustration


Product may differ from Image


General data

Dimensions H×W×D 88×51×30 mm

RJ45

Operating current (UL Rating) max. 175 mA

Locking of ports Snap In

Connection front side RJ45

Connection rear side RJ45

Operating voltage (UL Rating) max. 30 V AC/42.4 V DC

Specification CAT5e, Class D, 100 MHz, (EN 50173-1)

USA

Operating current 15 A

Operating voltage 125 V AC

No. of poles 2 + PE

Connection Plug-solder connection: 4.8×0.5 mm

SUB-D25

Locking of ports UNC 4...40 bolt

Operating current 3 A

Connection rear side SUB-D (male)

Connection front side SUB-D (female)

Operating voltage 48 V AC/DC

Operating current (UL Rating) max. 175 mA

Operating voltage (UL Rating) max. 30 V AC/42.4 V DC

No. of poles	25-pole
Product article number of manufacturer	4000-68000-4000000