

## MODLINK MSDD DATA INSERT

1×SUB-D9 female/S + 1×SUB-D9 male/female + 1×RJ45

RJ45; USB (A); SUB-D9; SUB-D9  
 1× RJ45, 8-pole metal, CAT5e (female/female)  
 1× USB 2.0 (female/female) form A  
 1× SUB-D9 (female/male)  
 1× SUB-D9 (male/female)

### [Link to Product](#)

#### Illustration



Product may differ from Image

#### General data

Dimensions H×W×D 88×51×45 mm

#### RJ45

Operating current (UL Rating)	max. 175 mA
Locking of ports	Snap In
Connection front side	RJ45
Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)

#### SUB-D9

Operating current (UL Rating)	max. 175 mA
Locking of ports	UNC 4...40 bolt
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Operating current	3 A
No. of poles	9-pole
Operating voltage	48 V AC/DC

#### USB

Operating current	max. 500 mA
Specification	USB: 2.0 (max. 480 Mbit/s)
Locking of ports	Snap In
Operating voltage	48 V AC/DC
Operating voltage (UL Rating)	42.4 V DC

Product article number of manufacturer 4000-68000-1240000