


Modlink MSDD-set: Frame 4000-68123-0000000,
 insert 4000-68000-3250000 + 4000-68000-1410000

[Link to Product](#)

Illustration



Product may differ from Image

Frame	
suitable for mounting with wall thickness	1...5 mm
Protection	IP65
Temperature range	-10...+60 °C (storage temperature -25...+60 °C)
Housing	Zinc die-casting, with surface finishing
RJ45	
Operating current (UL Rating)	max. 175 mA
Locking of ports	Snap In
Connection front side	RJ45
Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)
SUB-D9	
Connection rear side	SUB-D (female)
Operating current (UL Rating)	max. 175 mA
Connection front side	SUB-D (female)
Locking of ports	UNC 4...40 bolt
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Operating current	3 A
No. of poles	9-pole
Operating voltage	48 V AC/DC
China (CCC)	
Operating current	10 A
Connection	Screw terminals: max. 2× 4 mm ² (single/stranded wire)
Operating voltage	250 V AC
No. of poles	2 + PE
Shielding plate	
Tightening torque	0.9 Nm ±0.1
Connection	Threaded hole M4
Product article number of manufacturer	
4000-68123-3251410	