

**Modlink MSDD-set: Frame 4000-68223-0000000,**  
insert 4000-68000-0020000 + 4000-68000-1700000

### [Link to Product](#)

#### Illustration



Product may differ from Image

|                                           |                                                                               |
|-------------------------------------------|-------------------------------------------------------------------------------|
| <b>Frame</b>                              |                                                                               |
| suitable for mounting with wall thickness | 1...5 mm                                                                      |
| Protection                                | IP65                                                                          |
| Temperature range                         | -10...+60 °C (storage temperature -25...+60 °C)                               |
| Housing                                   | Frame: zinc die-casting, with surface finishing, Lid: plastic, PC transparent |
| <b>RJ45</b>                               |                                                                               |
| Operating current (UL Rating)             | max. 175 mA                                                                   |
| Locking of ports                          | Snap In                                                                       |
| Connection front side                     | RJ45                                                                          |
| Connection rear side                      | RJ45                                                                          |
| Operating voltage (UL Rating)             | max. 30 V AC/42.4 V DC                                                        |
| Specification                             | CAT5e, Class D, 100 MHz, (EN 50173-1)                                         |
| <b>SUB-D9</b>                             |                                                                               |
| Connection rear side                      | SUB-D (male)                                                                  |
| Operating current (UL Rating)             | max. 175 mA                                                                   |
| Connection front side                     | SUB-D (female)                                                                |
| Locking of ports                          | UNC 4...40 bolt                                                               |
| Operating voltage (UL Rating)             | max. 30 V AC/42.4 V DC                                                        |
| Operating current                         | 3 A                                                                           |
| No. of poles                              | 9-pole                                                                        |
| Operating voltage                         | 48 V AC/DC                                                                    |
| <b>Germany (VDE)</b>                      |                                                                               |
| Connection                                | Screw terminals: max. 2× 6 mm <sup>2</sup> (AWG 10)                           |
| Operating voltage                         | 250 V AC                                                                      |
| No. of poles                              | 2 + PE                                                                        |
| Operating current                         | 16 A                                                                          |
| <b>Shielding plate</b>                    |                                                                               |
| Tightening torque                         | 0.9 Nm ±0.1                                                                   |
| Connection                                | Threaded hole M4                                                              |
| <b>SUB-D25</b>                            |                                                                               |
| Locking of ports                          | UNC 4...40 bolt                                                               |
| Operating current                         | 3 A                                                                           |
| Connection rear side                      | SUB-D (solder connection)                                                     |
| Connection front side                     | SUB-D (female)                                                                |
| Operating voltage                         | 48 V AC/DC                                                                    |
| Operating current (UL Rating)             | max. 175 mA                                                                   |
| Operating voltage (UL Rating)             | max. 30 V AC/42.4 V DC                                                        |
| No. of poles                              | 25-pole                                                                       |
| Product article number of manufacturer    | 4000-68223-0021700                                                            |