

Modlink MSDD-set: Frame 4000-68223-0000000,
insert 4000-68000-0030000 + 4000-68000-0410000

Link to Product

Illustration



Product may differ from Image

| | |
|---|---|
| Frame | |
| suitable for mounting with wall thickness | 1...5 mm |
| Protection | IP65 |
| Temperature range | -10...+60 °C (storage temperature -25...+60 °C) |
| Housing | Frame: zinc die-casting, with surface finishing, Lid: plastic, PC transparent |
| SUB-D9 | |
| Connection rear side | SUB-D (solder connection) |
| Operating current (UL Rating) | max. 175 mA |
| Connection front side | SUB-D (female) |
| Locking of ports | UNC 4...40 bolt |
| Operating voltage (UL Rating) | max. 30 V AC/42.4 V DC |
| Operating current | 3 A |
| No. of poles | 9-pole |
| Operating voltage | 48 V AC/DC |
| USA | |
| Operating current | 15 A |
| Operating voltage | 125 V AC |
| No. of poles | 2 + PE |
| Connection | Plug-solder connection: 4.8x0.5 mm |
| SUB-D25 | |
| Locking of ports | UNC 4...40 bolt |
| Operating current | 3 A |
| Connection rear side | SUB-D (solder connection) |
| Connection front side | SUB-D (female) |
| Operating voltage | 48 V AC/DC |
| Operating current (UL Rating) | max. 175 mA |
| Operating voltage (UL Rating) | max. 30 V AC/42.4 V DC |
| No. of poles | 25-pole |
| Product article number of manufacturer | 4000-68223-0030410 |