

S-Lamp 22 L M12(4)

Lamp

S-Lamp 22 L M12(4)

Lamp

Mounting hole 22,3 mm

Connection M12 (4-pin)

[Link to Product](#)**Illustration**

Product may differ from Image

Mechanical protection

UL Enclosure Type Rating (Front side) type 4X

Electrical data

Short-circuit current	1000 A
Kind of short circuit protective device	fuse 250 V / 0.1 A / 1.5 kA gG quick
Operating voltage of the luminous element	20...28 V
Rated surge voltage	800 V
Rated insulation voltage	250 V
Operating current	12 mA (24 V DC)

Ambient characteristics

Salt-spray resistance	IEC 60068-2-11
Installation height max.	≤ 2000 m
Relative humidity	≤ 93% @ 40 °C
storage temperature	-40...90 °C
operating temperature	-25...70 °C

Mechanical data

Grid min.	30 mm
Mounting hole	22,3 mm
Mounting depth	30,2 mm
Dimensions H×W×D	29,8 x 40 mm
Terminal	M12, 4-pole, A-coded
Fixing	Threaded ring
Housing	Plastic

Product article number of manufacturer 69065

Media

The information in this brochure has been compiled with the utmost care.
 Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com

Degree of protection (IP), front side	IP66, IP67, IP69
---------------------------------------	------------------

Protection class (IP), rear side	IP66, IP67
----------------------------------	------------

Mechanical data

Installation height	9,8 mm
---------------------	--------

Supply

Rated operating current I _e	0,01 A
--	--------

Mechanical data

Can be illuminated	yes
--------------------	-----

Collar shape	round
--------------	-------

Color	black
-------	-------

Collar color	black
--------------	-------

Color of illuminant	white
---------------------	-------

Type of the lamps	LED
-------------------	-----