

E-Stop 22 2NC M12(5)

Emergency-Stop

E-Stop 22 2NC M12(5)

Emergency-Stop

Mounting hole 22,3 mm

Connection M12 (5-polig)

[Link to Product](#)**Illustration**

Product may differ from Image

Mechanical protection

UL Enclosure Type Rating (Front side)	type 4X
Mechanical endurance	50000
Mechanical endurance B10	65000
Operating life B10d	84500 Cycles

Electrical data

Short-circuit current	1000 A
Kind of short circuit protective device	fuse 250 V / 0.1 A / 1.5 kA gG quick
Switching current	1...100 mA
Rated voltage UL 60947	≤ 30 V AC/DC
Switching voltage	1...35 V
Power rating (voltage dependent)	0,25 W
Rated surge voltage	2500 V
Rated insulation voltage	250 V

Ambient characteristics

Salt-spray resistance	IEC 60068-2-11
Installation height max.	≤ 2000 m
Relative humidity	≤ 93% @ 40 °C
storage temperature	-40...90 °C
operating temperature	-40...85 °C

Mechanical data

Grid min.	30 mm
Mounting hole	22,3 mm
Mounting depth	30,1 mm
Dimensions HxWxD	30 x 29,8 x 69,7 mm

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com

Fixing	Threaded ring
Contact material	Gold
Contact function	2 Ö
Housing	Plastic
Product article number of manufacturer	69051
Media	
Degree of protection (IP), front side	IP65
Protection class (IP), rear side	IP65, IP67
Mechanical data	
Installation height	39,6 mm
Supply	
Rated operating voltage (AC-15)	35 V
Rated operating voltage (DC-13)	35 V
Mechanical data	
Can be illuminated	no
Collar shape	round
Color	red
Collar color	yellow
Actuating function	latching