

MODLINK MSDD DATA INSERT

1×SUB-D9 fem./sold. + 1×RJ45 + 1×USB-A fem./fem.

- RJ45; USB (A); SUB-D9
- 1× RJ45, 8-pole metal, CAT5e (female/female)
 - 1× USB 2.0 (female/female) form A
 - 1× SUB-D9 (solder connection/female)

Link to Product

Illustration



Product may differ from Image

General data	
Dimensions H×W×D	88×51×45 mm
RJ45	
Operating current (UL Rating)	max. 175 mA
Locking of ports	Snap In
Connection front side	RJ45
Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)
SUB-D9	
Connection rear side	SUB-D (solder connection)
Operating current (UL Rating)	max. 175 mA
Connection front side	SUB-D (female)
Locking of ports	UNC 4...40 bolt
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Operating current	3 A
No. of poles	9-pole
Operating voltage	48 V AC/DC
USB	
Operating current	max. 500 mA
Specification	USB: 2.0 (max. 480 Mbit/s)
Locking of ports	Snap In
Operating voltage	48 V AC/DC
Operating voltage (UL Rating)	42.4 V DC
Shielding plate	

Tightening torque	0.9 Nm \pm 0.1
Connection	Threaded hole M4
Product article number of manufacturer	4000-68000-1460000