

MODLINK MSDD DATA INSERT

1xSUB-D25 female/female + 1xRJ45 + 1xRJ12

- RJ45; RJ12; SUB-D25  
1× RJ45, 8-pole metal, CAT5e (female/female)  
1× RJ12 (6-pole plastic)  
1× SUB-D25 (female/male)

Link to Product

Illustration



Product may differ from Image



General data	
Dimensions H×W×D	88×51×25 mm
RJ45	
Operating current (UL Rating)	max. 175 mA
Locking of ports	Snap In
Connection front side	RJ45
Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)
RJ12	
Operating voltage	max. 48 V AC/DC
Connection front side	RJ12
Connection rear side	RJ12
Locking of ports	Snap In
Operating current	max. 1 A
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Operating current (UL Rating)	max. 175 mA
SUB-D25	
Locking of ports	UNC 4...40 bolt
Operating current	3 A
Connection rear side	SUB-D (male)

Connection front side	SUB-D (female)
Operating voltage	48 V AC/DC
Operating current (UL Rating)	max. 175 mA
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
No. of poles	25-pole
Product article number of manufacturer	4000-68000-1100000