

**M12 male 0° / M8 female 0° A-cod.**

PVC 3x0.25 ye UL/CSA 0.6m

Male straight – female straight

M12 – M8, 3-pole





Art-No. 7005 - M12 Lite - (plastic hexagonal screw) on request


Art-No. 7005 - M8 Lite - (plastic hexagonal screw) on request

Plastic housings with good resistance against chemicals and oils.


The resistance to aggressive media should be individually tested for your application. Further details on request.

Further cable lengths on request.

[Link to Product](#)**Illustration**



Product may differ from Image



\* only for products with UL/CSA approved cable

#### Form

Form 40561

#### Technical Data

|                                           |                                                                         |
|-------------------------------------------|-------------------------------------------------------------------------|
| Operating voltage                         | max. 50 V AC/60 V DC                                                    |
| Operating voltage (only UL listed)        | max. 30 V AC/DC                                                         |
| Rated surge voltage                       | 1.5 kV                                                                  |
| Operating current per contact             | max. 4 A                                                                |
| Material group                            | IEC 60664-1, category I                                                 |
| Coding                                    | A-coded                                                                 |
| Locking of ports                          | Screw thread (M8/M12×1 mm) recommended torque 0.4/0.6 Nm, self-securing |
| Protection                                | IP65, IP66K, IP67 inserted and tightened (EN 60529)                     |
| Material                                  | PUR                                                                     |
| Locking material                          | Zinc die casting, matte nickel plated                                   |
| suitable for corrugated tube (internal Ø) | M12 (10 mm); M8 (6.5 mm)                                                |
| Compression gland                         | M8 (SW9), M12 (SW13)                                                    |

#### General data

|                   |                                                   |
|-------------------|---------------------------------------------------|
| Standards         | DIN EN 61076-2-101 (M12), DIN EN 61076-2-104 (M8) |
| Mounting method   | inserted, tightened                               |
| Material (gasket) | FKM                                               |
| Pollution Degree  | 3                                                 |
| Temperature range | -25...+85 °C, depending on cable quality          |

#### Cables

|                           |                                         |
|---------------------------|-----------------------------------------|
| Cable identification      | 010                                     |
| Cable Type                | 1 (PVC)                                 |
| Approval (cable)          | UL (AWM-Style 2464/1731), CSA           |
| Cable weight [g/m]        | 29,37 g                                 |
| Material (wire)           | Cu wire, bare                           |
| Resistor (core)           | max. 79 Ω/km (20 °C)                    |
| Single wire Ø (core)      | 0.15 mm                                 |
| Construction (core)       | 14× 0.15 mm (multi-strand wire class 5) |
| Diameter (core)           | 3× 0.25 mm²                             |
| AWG                       | similar to AWG 24                       |
| Material (wire isolation) | PVC                                     |

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com

|                                        |                                                |
|----------------------------------------|------------------------------------------------|
| Material property (wire isolation)     | CFC-, cadmium-, silicone- and lead-free        |
| Shore hardness (wire isolation)        | 45 ±5 D                                        |
| Wire-Ø incl. isolation                 | 1.25 mm ±5%                                    |
| Color/numbering of wires               | br, bk, bl                                     |
| Stranding combination                  | 3 wires twisted                                |
| Shield                                 | no                                             |
| Material (jacket)                      | PVC                                            |
| Material property (jacket)             | CFC-, cadmium-, silicone- and lead-free        |
| Shore hardness (jacket)                | 85 ±5 A                                        |
| Outer-Ø (jacket)                       | 4.5 mm ±5%                                     |
| Color (jacket)                         | yellow                                         |
| chemical resistance                    | good resistance to oil, gasoline and chemicals |
| thermal resistance                     | flame retardant UL 1581 VW1 / CSA FT1          |
| Nominal voltage                        | UL 300 V AC                                    |
| Test voltage                           | 2000 V AC                                      |
| Current load capacity                  | to DIN VDE 0298-4                              |
| Temperature range (fixed)              | -30...+80 °C                                   |
| Temperature range (mobile)             | -5...+80 °C                                    |
| Bend radius (fixed)                    | 5× outer Ø                                     |
| Bend radius (moving)                   | 10× outer Ø                                    |
|                                        |                                                |
| Product article number of manufacturer | 7000-40561-0100060                             |
| Cable length                           | 0,6 m                                          |