

## Cube67 Valve-Interface, I/O Extension Module

DO23, SMC, Sub-D 25 pol., 0,5m

Expansion module

DO23 - Valve (E) 0.5 m

Multipole plug (70 mA)


SMC - Series SV

Connection cables are in the online shop under "Connection Technology".

Housing fully potted.

### Link to Product

#### Illustration



Product may differ from Image



#### General data

Mounting method	2-hole screw mounting
Temperature range	0...+55 °C (storage temperature -20...+75 °C)
Protection	IP67
Dimensions HxWxD	150x30x34.5 mm

#### Output

Actuator supply UA	24 V DC (EN 61131-2), via system connection (max. 4 A)
Switching current per output	max. 0.5 A (short-circuit and overload protected)

#### Cables

No./diameter of wires	36x 0.14 mm <sup>2</sup>
Material (jacket)	PVC
Cable Length	0.5 m

#### Internal communication

LED display	US: sensor supply and internal supply voltage (green: OK); UA: actuator supply (green: OK)
Current consumption	max. 50 mA

#### Connections

Fieldbus	via internal system connection
Sensor-system/actuator supply	via internal system connection (max. 2x 4 A)

I/O ports	SMC - Series SV
-----------	-----------------

Product article number of manufacturer	5665604
--	---------

**Diagnostic**

Communication status	via LED
----------------------	---------

Diagnostic via LED	per module
--------------------	------------

Diagnostic via BUS	per module and channel
--------------------	------------------------

Actuator warning	per channel via BUS
------------------	---------------------

Monitoring - under voltage	yes
----------------------------	-----

Monitoring - no voltage	yes
-------------------------	-----

Short-circuit and overload	yes
----------------------------	-----