

Adaptor M12 Male / M12 Female

Buffer module for DO (Pin 4-3)

Adapter Male - female M12 - M12, 4-pole max. 2 A 11 μF

Link to Product

Illustration

	Male	Female
	4 3 2	3 0 0 4 2 0 0 1
	PIN 1: n.c.	PIN 1: n.c.
	PIN 2: n.c.	PIN 2: n.c.
	PIN 3: 0 V	PIN 3: 0 V
	PIN 4: DO	PIN 4: DO
	Male	Female
	4 3 2	3 0 0 4 2 0 0 1
35 (1.37)	PIN 1: 24 V DC	PIN 1: 24 V DC
48 (1.88)	PIN 2: Input 1X	PIN 2: Input 1X
- 77.2 (3.04)	PIN 3: GND	PIN 3: GND
	PIN 4: Input OX	PIN 4: Input OX

Product may differ from Image



Form	
Form	55112
Technical Data	
Operating voltage	24 V DC external (1830.2 V DC) EN 61131-2
Protection	IP67 inserted and tightened (EN 60529)
Capacity	11 μF

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com



Total current	max. 2 A
General data	
Temperature range	-30+70 °C (storage temperature -40+85 °C)
Relative humidity	≤ 85%
Product article number of manufacturer	55112

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com