

## IMPACT20 PROFINET IO, DIGITAL IN-/OUTPUT MODULE

8 digital inputs and 8 digital outputs

Digital inputs/outputs

DI8 DO8 - 2 A

Connection cables are in the online shop under "Connection Technology".


Housing fully potted.

### [Link to Product](#)

#### Illustration



Product may differ from Image



#### General data

Mounting method	DIN-rail mountable (EN 60715)
Temperature range	0...+55 °C (storage temperature -20...+70 °C)
Protection	IP20
Dimensions HxWxD	117x56x47 mm

#### Module supply

Operating voltage	24 V DC (EN 61131-2)
-------------------	----------------------

#### Output

Total current	max. 8 A
Switching current per output	max. 2 A (short-circuit and overload protected)

#### Input

Sensor supply US	24 V DC (EN 61131-2), max. 700 mA per module, short-circuit and overload protected
Type	for 3-wire sensors or mechanical switches, PNP

#### Connections

Fieldbus	Ethernet 10/100 Mbit/s; 2x RJ45 (female)
Sensor-system/actuator supply	6x spring clamp plug-in terminals, max. 2.5 mm <sup>2</sup> (max. 12 A)
I/O ports	18x spring clamp plug-in terminals, max. 2.5 mm <sup>2</sup> (max. 12 A)

#### PROFINET

Addressing	DCP
------------	-----

Product article number of manufacturer 56921

**Diagnostic**

Communication status	via LED
Diagnostic via LED	per module and channel
Diagnostic via BUS	per module and channel
Monitoring - under voltage	yes
Monitoring - no voltage	yes
Short-circuit and overload	yes