

MASI68 I/O EXTENSION MODULE


8 digital inputs

Expansion module DI8 - 0.19 A (E) - 8× M8 (AB) Connection cables are in the online shop under "Connection Technology". Housing fully potted.

Link to Product

Illustration





Product may differ from Image



chnical Dat T

Technical Data	
ASI-Power 24	yes
Bus voltage (AS-Interface)	26.531.6 V DC
Profile (IO/ID/ID2 code)	2× S-0.A.E
Addressing	via master or M12 connection and programming device, presetting 1× address 31 A, 1× address 31 B
Address range	162 (131 A or B)
Total current	max. 300 mA
General data	
Mounting method	screw fixing
Temperature range	-20+60 °C (storage temperature -20+70 °C)
Protection	IP68
Dimensions H×W×D	85×30×34.5 mm
Input	
Sensor supply US	max. 190 mA from AS-Interface (short-circuit and overload protected)
Туре	for 3-wire sensors or mechanical switches, PNP
Connections	
Fieldbus	A-coded
I/O ports	M8, 3-pole
Product article number of manufacturer	56436
Diagnostic	

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com



Communication status	via LED
Diagnostic via LED	per module
Monitoring - no voltage	yes

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com