

MASI67 INSTALLATION TECHNOLOGY


Converter 2x profile cable to M12 male


MASI67 converter 2× profile cable to M12 (male) Connection cables are in the online shop under "Connection Technology".

Link to Product

Illustration







Product may differ from Image



Technical De

Technical Data	
Operating voltage	max. 36 V DC
Total current	max. 4 A
General data	
Mounting method	DIN-rail mountable (EN 60715) or screw fixing
Temperature range	-20+60 °C (storage temperature -40+80 °C)
Test isolation voltage	AS-Interface/Power 200 V, (EN 60664-1)

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com



Protection	IP67	
Dimensions H×W×D	90×74×39 mm	
Contact Layout		
PIN 1	AS-Interface + (brown)	
PIN 2	0 V (blue)	
PIN 3	AS-Interface - (blue)	
PIN 4	+24 V (brown)	
PIN 5	n.c.	

Product article number of manufacturer 55038

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com