

IMPACT67 Pro EC DIO8 IOL8 M12L 5P

EtherCAT, compact module, plastic

Digital inputs/outputs

IO-Link Master V1.1.3

M12 Power, 5-pole, L-coded


M12, 5-pole, A-coded

Housing fully potted.

Connection cables are in the online shop under "Connection Technology".

[Link to Product](#)**Illustration**

Product may differ from Image

**General data**

Mounting method	2-hole screw mounting, compatible with I/O modules of MVK model range
Temperature range	-25...+70 °C (storage temperature -40...+80 °C)
Protection	IP67
Dimensions HxWxD	37x63x225 mm

Output

Actuator supply UA	24 V DC (EN 61131-2), max. 10 A Port X0...X7
Switching current per output	max. 2 A per pin (short-circuit and overload-protected), max. 4 A per port

Input

Sensor supply US	24 V DC (EN 61131-2), max. 2 A load per port, short-circuit and overload protected, total max. 10 A port X0...X7
Type	for 3-wire sensors or mechanical switches, PNP, IO-Link Devices

IIoT Functions

IIoT Interfaces	yes (OPC UA, MQTT, JSON REST API)
Web interface	yes
Monitoring - temperature	yes
Monitoring - energy	yes (current and voltage)

IO-Link

Port Class	Class A + B (not galvanically separated)
IO-Link	8x Master

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com

Transfer parameters	32 Byte (In) 32 Byte (Out) per IO-Link port
Operating modes	COM1; COM2; COM3 (automatic)
Parameterization	
PIN 4	Input/output (port X0...X7); IO-Link master (port X0...X7)
PIN 2	Input/Output (port X0...X7); U-Actuator IO-Link Class B (port X0...X7)
Connections	
Fieldbus	Ethernet 10/100 Mbit/s; M12, D-coded
Sensor-system/actuator supply	M12 Power, 5-pole, L-coded, 2× max. 16 A
I/O ports	M12, 5-pole, A-coded
EtherCAT	
Addressing	automatic or Device ID by rotary switch
FMMU	8
SYNC manager	4
	ESM; EMCY
Protocols	CoE; FoE; EoE; AoE
Product article number of manufacturer	54632
Diagnostic	
Communication status	via LED
Diagnostic via LED	per module and channel
Diagnostic via BUS	per module and channel
Actuator warning	per channel via LED and BUS
Monitoring - under voltage	yes
Monitoring - no voltage	yes
Cable break	per port