



EXACT8, 10XM8, 4POLE, MOULDED CABLE

5.0m PUR 20x0,34+2x0,75


10-way, 4-pole
for NPN signals 24 V DC
Further cable lengths on request.
Plastic housings with good resistance against chemicals and oils.
The resistance to aggressive media should be individually tested for your application. Further details on request.

Link to Product

Illustration



Product may differ from Image



Form	
Form	80111
Technical Data	
Operating voltage	24 V DC
Operating current per contact	max. 2 A

Locking of ports	Screw thread (M8×1 mm)
Protection	IP65/IP67
Housing	Plastic, flame retardant
Signal per port	2
Total current	max. 8 A

General data

Temperature range	-20...+80 °C, depending on cable quality
-------------------	--

Cables

No./diameter of wires	20× 0.34 + 2× 0.75 mm ²
C-track properties	5 Mio.
Outer Ø	11.3 mm ±5%
Cable number	411
Approval (cable)	UL (AWM-Style 20233), CSA
Jacket Color	gray
Temperature range (fixed)	-40...+80 °C
Temperature range (mobile)	-5...+60 °C
Bend radius (fixed)	5× outer Ø
Bend radius (moving)	10× outer Ø
Material (jacket)	PUR (UL/CSA)

Contact Layout

PIN 1	(+)
PIN 2	(NC)/(S2)
PIN 3	(-)
PIN 4	(NO)/(S1)
LED (green): Power / LED (yellow): (S1) / LED (white): Signal (S2)	

Product article number of manufacturer	8000-80111-4110500
--	--------------------