

EXACT8, 4XM8, 3 POLE PRE-WIRED CABLE

15.0m PUR/PVC 4\*0,34+2\*0,75

PUR/PVC  
4-way, 3-pole  
15.0 m  
Further cable lengths on request.  
Plastic housings with good resistance against chemicals and oils.  
The resistance to aggressive media should be individually tested for your application. Further details on request.

Link to Product

Illustration



Product may differ from Image



Form	
Form	84010
Technical Data	
Operating voltage	24 V DC
Operating current per contact	max. 2 A

Locking of ports	Screw thread (M8×1 mm)
Protection	IP65/IP67
Housing	Plastic, flame retardant
Signal per port	1 - (31-32)
Total current	max. 8 A

#### General data

Temperature range	-20...+80 °C, depending on cable quality
-------------------	--

#### Cables

No./diameter of wires	4× 0.34 + 2× 0.75 mm <sup>2</sup>
Wire isolation	PVC (br, bl, ye, wh, gn, gr)
C-track properties	2 Mio.
Outer Ø	6.9 mm ±5%
Cable number	337
Color (jacket)	gray
Jacket Color	gray
Temperature range (fixed)	-30...+80 °C
Temperature range (mobile)	-5...+60 °C
Bend radius (fixed)	5× outer Ø
Bend radius (moving)	10× outer Ø
Material (jacket)	PUR/PVC

#### Contact Layout

PIN 1	(+)
PIN 3	(-)
PIN 4	(NO)/(S1)
	LED (green): Power / LED (yellow): (S1)

Product article number of manufacturer	8000-84010-3371500
--	--------------------