

MVP12, 8XM12, 5POLE, PLUG. TERM.

W/o cap, with pot. separation, NPN-LED's

8-way, 5-pole
Potential separation as option
with LED for digital NPN-signals 24 V DC
Plastic housings with good resistance against chemicals and oils.
The resistance to aggressive media should be individually tested for your application. Further details on request.
Further cable lengths on request.

Link to Product

Illustration



Product may differ from Image



Technical Data	
Operating voltage	24 V DC
Operating current per contact	max. 4 A
Locking of ports	Screw thread (M12×1 mm)

Protection	IP67 inserted and tightened (EN 60529)
------------	--

Housing	Plastic, flame retardant
---------	--------------------------

Signal per port	2
-----------------	---

Total current	max. 2× 8 A
---------------	-------------

General data

Temperature range	-20...+80 °C
-------------------	--------------

Dimensions H×W×D	149.2×50.2×16.5 mm
------------------	--------------------

Contact Layout

PIN 1	(+)
-------	-----

PIN 2	(NC)/(S2)
-------	-----------

PIN 3	(-)
-------	-----

PIN 4	(NO)/(S1)
-------	-----------

PIN 5	(Earth)
-------	---------

	LED (green): Power / LED (yellow): (S1/S2)
--	--

Product article number of manufacturer	276565
--	--------