



MVP-METALL, 4XM12, 5POL, LTG.FEST

15.0m PUR 8x0,34+3X0.75, UL/CSA


15.0 m
4-way, 5-pole
Replaces identical product (Art.No. 27484)
shielded
with LED for digital PNP-signals 24 V DC
Further cable lengths on request.

Link to Product

Illustration



Product may differ from Image



Technical Data

Operating voltage	24 V DC
Operating current per contact	max. 4 A
Locking of ports	Screw thread (M12x1 mm)
Protection	IP65, IP67, IP68

Housing Zinc die casting, matte nickel plated

General data

Temperature range -20...+90 °C, depending on cable quality

Cables

No./diameter of wires 8× 0.34 + 3× 0.75 mm²

Wire isolation TPE (grpk, wh, rdbl, gn, whgn, ye, brgn, gr, br, bl, gnye)

C-track properties 5 Mio.

Outer Ø 9.3 mm ±5%

Cable number 373

Shield yes

Color (jacket) gray

Jacket Color gray

Temperature range (fixed) -40...+90 °C

Temperature range (mobile) -40...+90 °C

Bend radius (fixed) 10× outer Ø

Bend radius (moving) 12× outer Ø

Material (jacket) PUR (UL/CSA)

Contact Layout

PIN 1 (+)

PIN 2 (NC)/(S2)

PIN 3 (-)

PIN 4 (NO)/(S1)

PIN 5 (Earth)

LED (green): Power / LED (yellow): (S1/S2)

Product article number of manufacturer 8000-54513-3731500