

## **CAP FOR D-BOX M12 4-WAY 5-POLE**

Pot.-sep. 30m PUR/PVC, 8x0,34+5X0.75

30.0 m for 4-way distribution boxes, 5-pole PUR/PVC potentially separated Further cable lengths on request.


Plastic housings with good resistance against chemicals and oils.


The resistance to aggressive media should be individually tested for your application. Further details on request.

## **Link to Product**

## Illustration







Product may differ from Image

Form	
Form	84659
Technical Data	
Housing	Plastic, flame retardant
Total current	max. 8 A
General data	
Temperature range	-20+80 °C, depending on cable quality
Cables	

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2022-11-13



## stay connected

No./diameter of wires	8× 0.34 + 5× 0.75 mm <sup>2</sup>
Wire isolation	PVC
C-track properties	1.5 Mio.
Outer Ø	9.2 mm ±5%
Cable number	374
Color (jacket)	gray
Jacket Color	gray
Temperature range (fixed)	-30+80 °C
Temperature range (mobile)	-30+80 °C
Bend radius (fixed)	10× outer Ø
Bend radius (moving)	12× outer Ø
Material (jacket)	PUR/PVC
Product article number of manufacturer	8000-84659-3743000