

Modular Filters

BANTAM Series, Flow to 30 scfm, Port Sizes 1/8 to 1/4



Thank You! You have just purchased a premium-quality ROSS® Air Preparation product. With care in its installation and maintenance, you can expect it to have a long and economical service life. Before you go any further, please take a few minutes to look over this information, then save it for future reference and for the useful service information it contains.

OPERATION

Manual drains must be periodically drained of accumulated liquids.

For Plastic Bowls with Manual or Automatic Internal Drain, manually drain by pushing up on Drain Knob (#7).

For Metal Bowls with Manual or Automatic Internal Drain, manually drain by turning Drain Knob (#7) counter-clockwise.



INSTALLATION

Please read and make sure you understand all installation instructions before proceeding with the installation.

If you have any questions about installation or servicing your product, please contact ROSS or your authorized ROSS distributor, see contact information listed at the back of this document, or visit www.rosscontrols.com to find your distributor.

1. Depressurize and lockout air pressure.
2. Upstream pipes must be free of excessive dirt and liquids.
3. Install the Filter in airline as near as possible to the device it is to serve.
4. Install the Filter so air flows in same direction as arrow on head.
5. Filter should be installed before any Regulator, Lubricators or Valves in airline.

SERVICE

If you need to service your product, turn off any electrical power to the system, shut off the air supply, exhaust the air in the system, and lock-out all power sources before beginning any disassembly operation.




TO CLEAN OR REPAIR:

Depressurize and lockout air pressure. Remove Bowl Assembly (#4 or #8 or #9 or N.S.) by turning counter-clockwise. Remove Filter Element (#3) by turning Stem (#5) counter-clockwise. Do not clean white polyethylene elements, they must be replaced. Sintered Bronze elements may be cleaned by soaking several hours in a suitable solvent, then blowing them out with compressed air, in reverse direction to normal air flow.

To service automatic internal drain: Remove Bowl Assembly (#4 or #9) by turning counter-clockwise, then remove Piston Drain top (#6). Clean Bowl Assembly (#4 or #9) and Piston Drain top (#6) with soap and water, then reassemble.

If the Filter cannot be repaired by cleaning with soap and water, the parts should be replaced. Plastic bowls may be cleaned with soap and water. Replace plastic bowls with metal if any signs of crazing or cracking are observed.

KEY	DESCRIPTION
1	Cover
2	Head
3	Filter Element
4	AID Bowl Assembly, Plastic
5	Stem
6	Piston Drain Top
7	Drain Knob
8	Manual Bowl Assembly, Plastic
9	AID Bowl Assembly, Metal
Not Shown	Manual Bowl Assembly, Metal



Plastic Bowl
Automatic Internal Drain

STANDARD SPECIFICATIONS

Construction: Fiber.

Ambient/Media Temperature:

Polycarbonate bowl: 40° to 125°F (4° to 52°C).

Metal bowl: 40° to 150°F (4° to 66°C).

Fluid Media: Compressed air.

Inlet Pressure - Automatic drain model:

Polycarbonate bowl: Up to 150 psig (up to 10 bar).

Metal bowl: Up to 200 psig (up to 14 bar).

Inlet Pressure - Manual drain model:

Polycarbonate bowl: 0 to 150 psig (0 to 10 bar).

Metal bowl: 0 to 200 psig (0 to 14 bar).

Filter Element: 5-micron rated polyethylene.

Body: Acetal.

Bowl: Polycarbonate or aluminum.

Seals: Nitrile.

IMPORTANT NOTE: Please read carefully and thoroughly all the **CAUTIONS** and **WARNINGS** on page 2.

REPLACEMENT PARTS



Bowl Assembly	Part Number	Contents	Filter Element	Material	Part Number
Automatic Internal Drain Bowl Kit, Plastic	920K77	Bowl, Knob, Drain Housing, Drain Plug, Piston Drain Top, Seal, and O-rings	Filter Element Kit, 5-µm	Polyethylene	933K77
Manual Drain Bowl Kit, Plastic	921K77	Bowl, Knob, Drain Plug, O-rings	Filter Element Kit, 5-µm	Sintered Bronze	R-KA130-27E5
Automatic Internal Drain Bowl Kit, Metal	R-ABFD130-22	Bowl, Auto Drain Stem, Knob, Drain Housing, Piston, Top, Seal, and O-rings	Optional Filter Element Kit, 20-µm		R-KA130-27E4
Manual Drain Bowl Kit, Metal	R-ABF130-22	Bowl, Drain Stem, Knob, and O-rings	Optional Filter Element Kit, 40-µm		R-KA130-27E3

LUBRICANTS, POLYCARBONATE BOWL CAUTIONS

COMPATIBLE LUBRICANTS

Although air line lubrication is not required for most ROSS valves, other mechanisms in the system may need such lubrication. When a lubricator is used, it should be supplied only with oils which are compatible with the materials used in the valves for seals and poppets. Generally speaking, these are petroleum base oils with oxidation inhibitors, and aniline point between 180°F (82°C) and 220°F (104°C) and an ISO 32, or lighter, viscosity. Oils with phosphate type additives, such as zinc dithiophosphate, must be avoided because they can harm polyurethane valve components. The best oils to use in pneumatic systems are those specifically compounded for air line lubricator service.

CAUTIONS ON THE USE OF POLYCARBONATE BOWLS

Use Only with Compressed Air. Filters and lubricators with polycarbonate bowls are specifically designed for compressed air service, and their use with any other fluid (liquid or gas) is a misapplication. The use with or injection of certain hazardous fluids in the system (e.g., alcohol or liquefied petroleum gas) could be harmful to the polycarbonate bowl or result in a combustible condition or hazardous leakage. Before using with a fluid other than air, or for nonindustrial applications, or for life support systems, consult ROSS.

Use Metal Bowl Guard When Supplied. A metal bowl guard is supplied with all but the smallest bowls, and must always be used to minimize danger from fragmentation in the event of failure of a polycarbonate bowl.

Avoid Harmful Substances. Some compressor oils, chemical cleaners, solvents, paints, and fumes will attack polycarbonate bowls and can cause bowl failure. Do not use with or near these materials. When a bowl becomes dirty, replace the bowl or wipe it with a clean dry cloth. Immediately replace any polycarbonate bowl which is crazed, cracked, or deteriorated.

SUBSTANCES HARMFUL TO POLYCARBONATE BOWLS

Acetaldehyde	Benzyl alcohol	Cresol	Ethylene dichloride	Milk of lime (CaOH)	Sodium sulfide
Acetic acid	Brake fluids	Cyclohexanol	Ethylene glycol	Nitric acid	Styrene
Acetone	Bromobenzene	Cyclohexanone	Formic acid	Nitrobenzene	Sulfuric acid
Acrylonitrile	Butyric acid	Cyclohexene	Freon (refrigerant & propellant)	Nitrocellulose lacquer	Sulfural chloride
Ammonia	Carbolic acid	Dimethyl formamide	Gasoline (high aromatic)	Perchlorethylene	Tetrahydronaphthalene
Ammonium fluoride	Carbon disulfide	Dioxane	Hydrazine	Phenol	Thiophene
Ammonium sulfide	Carbon tetrachloride	Ethane tetrachloride	Hydrochloric acid	Phosphorous hydroxyl chloride	Toluene
Anaerobic adhesives & sealants	Caustic potash solution	Ethyl acetate	Lacquer thinner	Phosphorous trichloride	Turpentine
Antifreeze	Caustic soda solution	Ethyl ether	Methyl alcohol	Propionic acid	Xylene
Benzene	Chlorobenzene	Ethylamine	Methylene chloride	Pyridine	
Benzoic acid	Chloroform	Ethylene chlorohydrin	Methylene salicylate	Sodium hydroxide	

TRADE NAMES OF SUBSTANCES HARMFUL TO POLYCARBONATE BOWLS

- Atlas Perma-Guard • Buna N • Cellulube #150 & #220 • Crylex #5 cement • Eastman 910 • Garlock 98403 (polyurethane) • Haskel 568-023
- Hilgard Company's hil phene • Houghton & Co. oil 1120, 1130, 1055 • Houtosafe 1000 • Kano Kroil • Keystone penetrating oil #2
- Loctite 271, 290, 601 • Loctite Teflon sealant • Marvel Mystery Oil • Minn. Rubber 366Y • National Compound N11 Nylock VC-3
- Parco 1306 Neoprene • Permabond 910 • Petron PD287 • Prestone • Pydraul AC • Sears Regular Motor Oil • Sinclair oil "Lily White"
- Stauffer Chemical FYRQUEL 150 • Stillman SR 269-75 (polyurethane) • Stillman SR 513-70 (neoprene) • Tannergas • Telar
- Tenneco anderol 495 & 500 oils • Titon • Vibra-tite • Zerec

STANDARD WARRANTY

under this warranty is limited to repair or replacement of the product or refund of the purchase price paid solely at the discretion of ROSS and provided such product is returned to ROSS freight prepaid and upon examination by ROSS is found to be defective. This warranty becomes void in the event that product has been subject to misuse, misapplication, improper maintenance, modification or tampering.

THE WARRANTY EXPRESSED ABOVE IS IN LIEU OF AND EXCLUSIVE OF ALL OTHER WARRANTIES AND ROSS EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES EITHER EXPRESSED OR IMPLIED WITH RESPECT TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. ROSS MAKES NO WARRANTY WITH RESPECT TO ITS PRODUCTS MEETING THE PROVISIONS OF ANY GOVERNMENTAL OCCUPATIONAL SAFETY AND/OR HEALTH LAWS OR REGULATIONS. IN NO EVENT IS ROSS LIABLE TO PURCHASER, USER, THEIR EMPLOYEES OR OTHERS FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES WHICH MAY RESULT FROM A BREACH OF THE WARRANTY DESCRIBED ABOVE OR THE USE OR MISUSE OF THE PRODUCTS. NO STATEMENT OF ANY REPRESENTATIVE OR EMPLOYEE OF ROSS MAY EXTEND THE LIABILITY OF ROSS AS SET FORTH HEREIN.

ROSS CONTROLS	USA	TEL: 1-248-764-1800	www.rosscontrols.com
ROSS EUROPA GmbH	Germany	TEL: 49-6103-7597-0	www.rosseuropa.com
ROSS ASIA K.K.	Japan	TEL: 81-42-778-7251	www.rossasia.co.jp
ROSS UK Ltd.	UK	TEL: 44-1543-671495	www.rossuk.co.uk
ROSS SOUTH AMERICA Ltda.	Brazil	TEL: 55-11-4335-2200	www.rosscontrols.com.br
ROSS CONTROLS INDIA Pvt. Ltd.	India	TEL: 91-44-2624-9040	email: ross.chennai@rosscontrols.com
ROSS CONTROLS (CHINA) Ltd.	China	TEL: 86-21-6915-7961	www.rosscontrolschina.com
ROSS FRANCE S.A.S.	France	TEL: 33-1-49-45-65-65	www.rossfrance.com
ROSS CANADA (6077170 CANADA INC. AN INDEPENDENT REPRESENTATIVE)	Canada	TEL: 1-416-251-7677 (ROSS)	www.rosscanada.com