



SAFE AIR ENTRY ASSEMBLIES WITH M35 SERIES VALVES

PRODUCT CATALOG



Safe Air Entry Assemblies with M35 Series Double Valves

Product Overview

Air entry assembly for Pneumatic Control and Air Dump/Release applications.




Illustration examples.

Air entry system via a manual Lockout L-O-X® valve, air preparation FRL combinations, and an M35 Series Safe Exhaust double valve with or without Soft-Start function.

ROSS systems have the same quality that you have come to expect from ROSS components. Units are fully configurable, tested, and ready for quick and easy installation at the job site.

Mounting accessories are used for modular connection to ROSS MD Series Filter-Regulator units. Bracket, Screw, Clamp and Mounting Adapter required for mounting.

ASSEMBLY COMPONENTS & FEATURES

Energy Isolation Lockout L-O-X® Valve 15 Series

- 3/2 valve
- Classic L-O-X® or Modular L-O-X®
- Lockable only in the OFF position
- Has a full size exhaust port (equal to or larger than supply)
- Simple push/pull of the large handle provides positive direct manual operation
- Fluorocarbon slipper seals for easy shifting, even after long periods of inactivity
- Integrated sensing port for pressure verification or visual indicator
- High flow, clog resistant; silencers included

Integrated Filter/Regulator Filter/Regulator, and Lubricator MD4™ Series

- Lubricator with metal bowl
- Integrated Filter/Regulator (Filter and Pressure Regulator combined into a single unit) with high-strength polycarbonate plastic bowl
- 5-micron filter element
- Automatic filter drain
- Self relieving regulator
- Analog gauge

Control Reliable Safe Exhaust Double Valve M35 Series

- 3/2 valve
- Valve have both modular receptacles, and female threaded ports, which allows either modular connection or direct piping
- Pressure sensors - for external monitoring of valve state
- Integrated EEZ-ON® (Soft-Start) module option, allows slower build-up of pressure during start-up
- LED indicators - aid troubleshooting
- Built-in silencer





Mounting

Modular or direct piping assembly.

SISTEMA Library

Available for download at rosscontrols.com.

M35 SERIES VALVE PRODUCT CREDENTIALS

Safety Category	DGVU (German Social Accident Insurance)	Declaration of Conformity			ISO Standard	CSA Certificate of Compliance	CRN Certification
 		CE	UKCA	EAC	ISO 13849-1:2015		Available for appropriately tested valves

NOTE: Per specifications and regulations, lockout L-O-X® products are defined as energy isolation devices, NOT AS EMERGENCY STOP DEVICES. These valve assemblies are not designed for controlling clutch/brake mechanisms on mechanical power presses.

MODEL NUMBER CONFIGURATOR

with 3-Way 2-Position Valves

M35
Series

S
Lockout Valve*

L
Classic L-O-X®

F
Modular L-O-X®

2U
None

40
* Silencer Included.

G
Thread
G
NPT

A
Monitoring
External

E
Communication
None

X
Voltage
24 V DC

AA
Pressure Measuring Device
(for M35 Series valve)

G
Analog Gauge

A
Digital Transducer

A
None (plugged port)

M35 Series Valve Soft-Start Option	
With Soft-Start	S
Without Soft-Start	X

Lockout Valve*	
Classic L-O-X®	L
Modular L-O-X®	M
None	X


Filter, Regulator, Lubricator	
Integrated Filter/Regulator	F
Filter and Regulator	R
Integrated Filter/Regulator, and Lubricator	L

Extra Port Block (in relation to M35 valve)		
Location	Size	
Upstream	1/4	2U
Upstream	3/8	3U
Upstream	1/2	4U
Downstream	1/4	2D
Downstream	3/8	3D
Downstream	1/2	4D


Extra Port Block (in relation to M35 valve)		
Location	Size	
Both	1/4	2B
Both	3/8	3B
Both	1/2	4B
None	NA	XX

Port Size		M35 Series Valve Exhaust Type	
In-Out	Exhaust		
1/2	—	Built-in Silencer	40
3/4	—	Built-in Silencer	50
1/2	1	Threaded Exhaust Flange*	46
3/4	1	Threaded Exhaust Flange*	56

Pin Configuration Combinations		
Solenoid	Sensor	
A	A	AA
A	B	AB
A	C	AC
C	C	CC
D	B	DB
D	C	DC



M35 Series Valve							
Port Size		Basic Size	Soft-Start	with Built-in Silencer		with Threaded Exhaust Flange	
				Flow C _v		Flow C _v	
1, 2	3			1-2	2-3	1-2	2-3
1/2 & 3/4	Built-in Silencer or 1" Threaded Exhaust Flange	8	With	4.1	7.5	4.1	7.57
			Without	4.3	7.5	4.3	7.57




Technical Data

Models with Classic Lockout L-O-X® Valve


DIMENSIONS

Inches (mm)

with MD4™ Integrated Filter/Regulator option, with or without Extra Port Blocks



with MD4™ Integrated Filter/Regulator and Lubricator option, with or without Extra Port Blocks



For additional information, and to assist you with piping and connectivity designs, our products are available in downloadable 2D drawings and 3D CAD models in a wide range of options including native formats, visit www.rosscontrols.com.

An Integration Guide for the M35 Series valves is available from ROSS to provide information such as operation & monitoring, and validation test procedure for valve operation and external monitoring logic.


[Integration Guide - M35 Series Safe Exhaust Double Valves](#)

Models with Classic Lockout L-O-X® Valve

DIMENSIONS

Inches (mm)

with MD4™ Filter and Regulator option, with or without Extra Port Blocks



For additional information, and to assist you with piping and connectivity designs, our products are available in downloadable 2D drawings and 3D CAD models in a wide range of options including native formats, visit www.rosscontrols.com.

An Integration Guide for the M35 Series valves is available from ROSS to provide information such as operation & monitoring, and validation test procedure for valve operation and external monitoring logic.

Integration Guide - M35 Series Safe Exhaust Double Valves


Assembly Technical Data

Models with Modular Lockout L-O-X® Valve


DIMENSIONS

Inches (mm)

with MD4™ Integrated Filter/Regulator option, with or without Extra Port Blocks



with MD4™ Integrated Filter/Regulator and Lubricator option, with or without Extra Port Blocks



For additional information, and to assist you with piping and connectivity designs, our products are available in downloadable 2D drawings and 3D CAD models in a wide range of options including native formats, visit www.rosscontrols.com.

An Integration Guide for the M35 Series valves is available from ROSS to provide information such as operation & monitoring, and validation test procedure for valve operation and external monitoring logic.


Integration Guide - M35 Series Safe Exhaust Double Valves

Models with Modular Lockout L-O-X® Valve

DIMENSIONS

Inches (mm)

with MD4™ Filter and Regulator option, with or without Extra Port Blocks



For additional information, and to assist you with piping and connectivity designs, our products are available in downloadable 2D drawings and 3D CAD models in a wide range of options including native formats, visit www.rosscontrols.com.

An Integration Guide for the M35 Series valves is available from ROSS to provide information such as operation & monitoring, and validation test procedure for valve operation and external monitoring logic.

[Integration Guide - M35 Series Safe Exhaust Double Valves](#)

Air Entry Assemblies with M35 Series Double Valves and Drip Leg Option

Product Overview

Air entry assembly for Pneumatic Control and Air Dump/Release applications.

Combination with Classic Lockout Valve



Combination with Modular Lockout Valve



Illustration examples.

Air entry system via an optional drip leg, with integrated filter/regulator “F/R” or an air filter and pressure regulator “FR”, manual Lockout L-O-X® valve, and an M35 Series Safe Exhaust double valve with or without Soft-Start function.

ROSS systems have the same quality that you have come to expect from ROSS components. Units are fully configurable, tested, and ready for quick and easy installation at the job site.

Two types of Lockout Valve - Air Preparation combinations offered:

Type C – with Classic Lockout L-O-X® valve, and filter (with metal bowl) and pressure regulator “FR”

Type M – with Modular Lockout L-O-X® valve, and integrated filter/regulator “F/R” with high-strength polycarbonate plastic bowl.

ASSEMBLY COMPONENTS & FEATURES

Drip Leg

- Inlet and Drain equipped with Ball Valves

Filter and Regulator

MD4™ Series

Filter/Regulator, and Lubricator

MD3™ Series

- Filter with metal bowl
- Integrated Filter/Regulator (Filter and Pressure Regulator combined into a single unit) with high-strength polycarbonate plastic bowl
- 5-micron filter element
- Automatic filter drain
- Self relieving regulator
- Analog gauge

Energy Isolation Lockout L-O-X® Valve

15 Series

- 3/2 valve
- Classic L-O-X® or Modular L-O-X®
- Lockable only in the OFF position
- Has a full size exhaust port (equal to or larger than supply)
- Simple push/pull of the large handle provides positive direct manual operation
- Fluorocarbon slipper seals for easy shifting, even after long periods of inactivity
- Integrated sensing port for pressure verification or visual indicator; Pop-Up indicator included
- High flow, clog resistant; silencers included

Control Reliable Safe Exhaust Double Valve

M35 Series

- 3/2 valve
- Pressure sensors - for external monitoring of valve state
- Integrated EEZ-ON® (Soft-Start) module option, allows slower build-up of during start-up
- LED indicators - aid troubleshooting
- Built-in silencer





Mounting

Modular or direct piping assembly, or plate mounted assembly option

SISTEMA Library

Available for download at rosscontrols.com.

M35 SERIES VALVE PRODUCT CREDENTIALS

Safety Category	DGV (German Social Accident Insurance)	Declaration of Conformity			ISO Standard	CSA Certificate of Compliance	CRN Certification
 		CE	UKCA	EAC	ISO 13849-1:2015		Available for appropriately tested valves

NOTE: Per specifications and regulations, lockout L-O-X® products are defined as energy isolation devices, NOT AS EMERGENCY STOP DEVICES. These valve assemblies are not designed for controlling clutch/brake mechanisms on mechanical power presses.

MODEL NUMBER CONFIGURATOR with 3-Way 2-Position Valves

RCM35 **S** **4** **G** **P** **D** **C** **AA** **A**

Series

M35 Series Valve Soft-Start Option

With Soft-Start	S
Without Soft-Start	X

Port Size

1/2	4
3/4	5

Thread

G	G
NPT	N

Plate

With	P
Without	X

Lockout L-O-X® Valve Type

Classic	Filter and Regulator	C
Modular	Integrated Filter/Regulator	M

Revision Level


Air Preparation Type

Drip Leg


With	D
Without	X

Pin Configuration Combinations*

Solenoid	Sensor	
A	A	AA
A	B	AB
A	C	AC
C	C	CC
D	B	DB
D	C	DC



M35 Series Valve							
Port Size		Basic Size	Soft-Start	with Built-in Silencer		with Threaded Exhaust Flange	
				Flow C _v		Flow C _v	
1, 2	3			1-2	2-3	1-2	2-3
1/2 & 3/4	Built-in Silencer or 1" Threaded Exhaust Flange	8	With	4.1	7.5	4.1	7.57
			Without	4.3	7.5	4.3	7.57




Technical Data


DIMENSIONS

Inches (mm)

Model with Filter and Regulator and Classic Lockout L-O-X® Valve option



Model with Integrated Filter/Regulator and Modular Lockout L-O-X® Valve option



For additional information, and to assist you with piping and connectivity designs, our products are available in downloadable 2D drawings and 3D CAD models in a wide range of options including native formats, visit www.rosscontrols.com.

An Integration Guide for the M35 Series valves is available from ROSS to provide information such as operation & monitoring, and validation test procedure for valve operation and external monitoring logic.

Integration Guide - M35 Series Safe Exhaust Double Valves

PRESSURE GAUGE

Analog Pressure Gauge	Mounting	Port Size	Thread Type	Model Number	Pressure Range psig (bar)	Case Diameter inches (mm)
	Center Back	1/8	Male	5400A1002	0-160 (0-11)	1.5 (38)

ENERGY RELEASE VERIFICATION


Visual Pressure Indicator	Verification Type	Installation Location	Indicator Type	Model Number	Port Thread
	Pneumatic	Pressure Sensing Port	Visual Pop-up Pin	988A30	1/8 NPT

Pressure Switch	Verification Type	Installation Location	Connector Type	Model Number	Factory Preset psi (bar)	Port Thread
	Electrical	Pressure Sensing Port	DIN EN 175301-803 Form A	586A86	5 (0.3) falling	1/8 NPT

Redundant Pressure Switch Assembly	Verification Type	Installation Location	Connector Type	Model Number	Factory Preset psi (bar)	Port Size
	Electrical (Dual)	Downstream	DIN EN 175301-803 Form A	RC026-13	5 (0.3) falling	3/8 NPT

Pressure Switch Pinout

DIN EN 175301-803 Form A



- 1 - Common
- 2 - Normally Closed
- 3 - Normally Open
- 4 - Ground (Not Used)


PRESSURE TRANSDUCERS

Digital Pressure Transducers	Monitoring Type	Electrical Connection	Electrical Output	Model Number		Pressure Port Size	Pressure Range psig (bar)	Weight lb (Kg)
				G Thread	NPT Thread			
	Electrical	M8, 4 Pin	(1) PNP with (1) 4-20ma	D760B94	760B94	1/8	0 to 145 (0 to 10)	0.099 (0.045)

For Digital Pressure Readout, Analog 4-20mA Output, and Transistor Switching Output.

Connector Pinout

Sensor Pinout with Analog Output




- 1 - Brown - 24 VDC
- 2 - White - 4 to 20mA
- 3 - Blue - 0 VDC
- 4 - Black PNP Open Collector Output 1

Accessories

PREWIRED ELECTRICAL CONNECTORS

Prewired Connector Kits	Cable						Kit Number
	End 1	End 2	Length meters (feet)	Connection	Quantity Included	Cord Diameter mm	Without Light
	Connector	Cord / Connector					
	M12, Female 5-pin straight A-coded	Flying Leads	5 (16.4)	Solenoid	1	6	2644B77
				Sensor	1	6	
			10 (32.8)	Solenoid	1	6	2370B77
				Sensor	1	6	
		Female Connector	5 (16.4)	Solenoid	1	6	2645B77
				Sensor	1	6	
			10 (32.8)	Solenoid	1	6	2371B77
				Sensor	1	6	

Connector Pinout



- 1 - Brown
- 2 - White
- 3 - Blue
- 4 - Black
- 5 - Grey

LOCKOUT DEVICE

Lockout Hasp	Valve Model Use	Model Number
	Manual Lockout L-O-X® Classic Style	356A30

EXHAUST SILENCERS

Silencers for Threaded Exhaust Flange Option	Port Size	Thread Type	Model Number		Flow Avg. C _v
			R/Rp Thread	NPT Thread	
	1	Male	D5500A6003	5500A6003	14.6

MODULAR CONNECTION

M35 Series valves have both modular receptacles for piping and female threaded ports inside receptacles, which allows either modular connection or direct piping. Mounting accessories listed below are used for modular connection to ROSS MD Series filter-regulator units.

Mounting Brackets & Clamp for Module Connections	Options		Model Number	
	Clamp only		R-A118-105	
	Bracket, Screw, and Clamp		R-A118-105M	

Port Block and End Ports	Options	Port Size	Model Number	
			G Thread	NPTF Thread
	Extra Port Blocks	1/2	R-118-106-4W	R-118-106-4
	Female End Ports	1/2	R-118-100-4W	R-118-100-4
		3/4	R-118-100-6W	R-118-100-6
	Male End Ports	1/2	R-118-109-4FW	R-118-109-4F
		3/4	R-118-109-6FW	R-118-109-6F

REPLACEMENT FILTER ELEMENTS

Filter Elements	Filter Series	Bowl Type	Element Material	Model Number		
				Element Rating		
				5-µm	20-µm	40-µm
	MD3™	Standard	Polyethylene	R-A60F-03PE5	—	—
			Sintered Bronze	R-A60F-03E5	R-A60F-03E4	R-A60F-03E3
	MD4™	Standard	Polyethylene	R-A115-106PE5	—	—
			Sintered Bronze	R-A115-106E5	R-A115-106E4	R-A115-106PE3



LUBRICANTS, POLYCARBONATE BOWL CAUTIONS

COMPATIBLE LUBRICANTS

Although air line lubrication is not required for most ROSS valves, other mechanisms in the system may need such lubrication. When a lubricator is used, it should be supplied only with oils which are compatible with the materials used in the valves for seals and poppets. Generally speaking, these are petroleum base oils with oxidation inhibitors, and aniline point between 180°F (82°C) and 220°F (104°C) and an ISO 32, or lighter, viscosity. Oils with phosphate type additives, such as zinc dithiophosphate, must be avoided because they can harm polyurethane valve components. The best oils to use in pneumatic systems are those specifically compounded for air line lubricator service.

CAUTIONS ON THE USE OF POLYCARBONATE BOWLS

Use Only with Compressed Air. Filters and lubricators with polycarbonate bowls are specifically designed for compressed air service, and their use with any other fluid (liquid or gas) is a misapplication. The use with or injection of certain hazardous fluids in the system (e.g., alcohol or liquefied petroleum gas) could be harmful to the polycarbonate bowl or result in a combustible condition or hazardous leakage. Before using with a fluid other than air, or for nonindustrial applications, or for life support systems, consult ROSS.

Use Metal Bowl Guard When Supplied. A metal bowl guard is supplied with all but the smallest bowls, and must always be used to minimize danger from fragmentation in the event of failure of a polycarbonate bowl.

Avoid Harmful Substances. Some compressor oils, chemical cleaners, solvents, paints, and fumes will attack polycarbonate bowls and can cause bowl failure. Do not use with or near these materials. When a bowl becomes dirty, replace the bowl or wipe it with a clean dry cloth. Immediately replace any polycarbonate bowl which is crazed, cracked, or deteriorated.

SUBSTANCES HARMFUL TO POLYCARBONATE BOWLS

Acetaldehyde	Carbon disulfide	Ethylene dichloride	Phosphorous trichloride
Acetic acid	Carbon tetrachloride	Ethylene glycol	Propionic acid
Acetone	Caustic potash solution	Formic acid	Pyridine
Acrylonitrile	Caustic soda solution	Freon (refrigerant & propellant)	Sodium hydroxide
Ammonia	Chlorobenzene	Gasoline (high aromatic)	Sodium sulfide
Ammonium fluoride	Chloroform	Hydrazine	Styrene
Ammonium hydroxide	Cresol	Hydrochloric acid	Sulfuric acid
Ammonium sulfide	Cyclohexanol	Lacquer thinner	Sulfural chloride
Anaerobic adhesives & sealants	Cyclohexanone	Methyl alcohol	Tetrahydronaphthalene
Antifreeze	Cyclohexene	Methylene chloride	Thiophene
Benzene	Dimethyl formamide	Methylene salicylate	Toluene
Benzoic acid	Dioxane	Milk of lime (CaOH)	Turpentine
Benzyl alcohol	Ethane tetrachloride	Nitric acid	Xylene
Brake fluids	Ethyl acetate	Nitrobenzene	Perchloroethylene
Bromobenzene	Ethyl ether	Nitrocellulose lacquer	
Butyric acid	Ethylamine	Phenol	
Carbolic acid	Ethylene chlorohydrin	Phosphorous hydroxyl chloride	

TRADE NAMES OF SUBSTANCES HARMFUL TO POLYCARBONATE BOWLS

Atlas Perma-Guard	Loctite Threadlocker Red 271	Pydraul AC
Buna-N	Loctite Threadlocker 290	Sears Regular Motor Oil
Cellulube #150 & #220	Loctite 601	Sinclair oil "Lily White"
Crylex #5 cement	Loctite Teflon sealant	Stauffer Chemical FYRQUEL 150
Eastman 910	Marvel Mystery Oil	Stillman #SR 269-75 (polyurethane)
Garlock #98403 (polyurethane)	Minnesota Rubber 366Y	Stillman #SR 513-70 (neoprene)
Haskel #568-023	National Compound #N11	Tannergas
Hilgard Company's Hil-Phene	Nylock VC-3	Telar
Houghton & Co. oil #1120, #1130, #1055	Parco #1306 Neoprene	Tenneco Anderol 495 & 500 oils
Houtosafe 1000	Permabond 910	Titon
Kano Kroil	Petron PD287	Vibra-TITE
Keystone penetrating oil #2	Prestone	Valvolin ZEREX

CAUTIONS, WARNINGS And STANDARD WARRANTY



ROSS OPERATING VALVE, ROSS CONTROLS®, ROSS DECCO®, and AUTOMATIC VALVE INDUSTRIAL, collectively the "ROSS Group".

PRE-INSTALLATION or SERVICE

1. Before servicing a valve or other pneumatic component, be sure all sources of energy are turned off, the entire pneumatic system is shut down and exhausted, and all power sources are locked out (ref: OSHA 1910.147, EN 1037).
2. All ROSS Group Products, including service kits and parts, should be installed and/or serviced only by persons having training and experience with pneumatic equipment. Because any product can be tampered with and/or need servicing after installation, persons responsible for the safety of others or the care of equipment must check ROSS Group Products on a regular basis and perform all necessary maintenance to ensure safe operating conditions.
3. All applicable instructions should be read and complied with before using any fluid power system to prevent harm to persons or equipment. In addition, overhauled or serviced valves must be functionally tested prior to installation and use. If you have any questions, call your nearest ROSS Group location.
4. Each ROSS Group Product should be used within its specification limits. In addition, use only ROSS Group components to repair ROSS Group Products.

WARNINGS:

Failure to follow these instructions can result in personal injury and/or property damage.

FILTRATION and LUBRICATION

1. Dirt, scale, moisture, etc., are present in virtually every air system. Although some valves are more tolerant of these contaminants than others, best performance will be realized if a filter is installed to clean the air supply, thus preventing contaminants from interfering with the proper performance of the equipment. The ROSS Group recommends a filter with a 5-micron rating for normal applications.
2. All standard ROSS Group filters and lubricators with polycarbonate plastic bowls are designed for compressed air applications only. Use the metal bowl guard, where provided, to minimize danger from high pressure fragmentation in the event of bowl failure. Do not expose these products to certain fluids, such as alcohol or liquefied petroleum gas, as they can cause bowls to rupture, creating a combustible condition and hazardous leakage. Immediately replace crazed, cracked, or deteriorated bowls.
3. Only use lubricants which are compatible with materials used in the valves and other components in the system. Normally, compatible lubricants are petroleum base oils with oxidation inhibitors, an aniline point between 180°F (82°C) and 220°F (104°C), and an ISO 32, or lighter, viscosity. Avoid oils with

phosphate type additives which can harm polyurethane components, potentially leading to valve failure which risks personal injury, and/or damage to property.

WARNINGS:

Failure to follow these instructions can result in personal injury and/or property damage.

AVOID INTAKE/EXHAUST RESTRICTION

1. Do not restrict air flow in the supply line. To do so could reduce the pressure of the supply air below minimum requirements for the valve and thereby causing erratic action.
2. Do not restrict a valve's exhaust port as this can adversely affect its operation. Exhaust silencers must be resistant to clogging and must have flow capacities at least as great as the exhaust capacities of the valves. Contamination of the silencer can result in reduced flow and increased back pressure.

WARNINGS: Failure to follow these instructions can result in personal injury and/or property damage.

SAFETY APPLICATIONS

1. Mechanical Power Presses and other potentially hazardous machinery using a pneumatically controlled clutch and brake mechanism must use a press control double valve with a monitoring device. A double valve without a self-contained monitoring device should be used only in conjunction with a control system which assures monitoring of the valve. All double valve installations involving hazardous applications should incorporate a monitoring system which inhibits further operation of the valve and machine in the event of a failure within the valve mechanism.
2. Safe Exhaust (dump) valves without a self-contained monitoring device should be used only in conjunction with a control system which assures monitoring of the valve. All Safe Exhaust valve installations should incorporate a monitoring system which inhibits further operation of the valve and machine in the event of a failure within the valve mechanism.
3. Per specifications and regulations, the ROSS L-O-X® and L-O-X® with EEZ-ON®, N06 and N16 Series operation products are defined as energy isolation devices, NOT AS EMERGENCY STOP DEVICES.

WARNINGS:

Failure to follow these instructions can result in personal injury and/or property damage.

STANDARD WARRANTY

All products sold by the ROSS Group are warranted for a one-year period [with the exception of Filters, Regulators and Lubricators ("FRLs") which are warranted for a period of seven (7) years] from the date of purchase. All products are, during their respective warranty periods, warranted to be free of defects in material and workmanship. The ROSS Group's obligation under this warranty is limited to repair, replacement or refund of the purchase price paid for products which the ROSS Group has determined, in its sole discretion, are defective. All warranties become void if a product has been subject to misuse, misapplication, improper maintenance, modification or tampering. Products for which warranty protection is sought must be returned to the ROSS Group freight prepaid.

THE WARRANTY EXPRESSED ABOVE IS IN LIEU OF AND EXCLUSIVE OF ALL OTHER WARRANTIES AND THE ROSS GROUP EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES EITHER EXPRESSED OR IMPLIED WITH RESPECT TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THE ROSS GROUP MAKES NO WARRANTY WITH RESPECT TO ITS PRODUCTS MEETING THE PROVISIONS OF ANY GOVERNMENTAL OCCUPATIONAL SAFETY AND/OR HEALTH LAWS OR REGULATIONS. IN NO EVENT IS THE ROSS GROUP LIABLE TO PURCHASER, USER, THEIR EMPLOYEES OR OTHERS FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES WHICH MAY RESULT FROM A BREACH OF THE WARRANTY DESCRIBED ABOVE OR THE USE OR MISUSE OF THE PRODUCTS. NO STATEMENT OF ANY REPRESENTATIVE OR EMPLOYEE OF THE ROSS GROUP MAY EXTEND THE LIABILITY OF THE ROSS GROUP AS SET FORTH HEREIN.





AMERICAS	ROSS CONTROLS	USA	Tel: +1-248-764-1800	www.rosscontrols.com
	ROSS CONTROLS CANADA Ltd.	Canada	Tel: +1-416-251-7677	www.rosscanada.com
	ROSS DO BRASIL EIRELI	Brazil	Tel: +55-11-4335-2200	www.rosscontrols.com.br
EUROPE	ROSS EUROPA GmbH	Germany	Tel: +49 (0)6103-7597-100	www.rosseuropa.com
	ROSS FRANCE SAS	France	Tel: +33-(0)1-49-45-65-65	www.rossfrance.com
	ROSS PNEUMATROL Ltd.	United Kingdom	Tel: +44 (0)1254 872277	www.rossuk.co.uk
ASIA & PACIFIC	ROSS CONTROLS INDIA Pvt. Ltd.	India	Tel: +91-44-2624-9040	www.rosscontrolsindia.com
	ROSS CONTROLS (CHINA) Ltd.	China	Tel: +86-21-6915-7961	www.rosscontrolschina.com
	ROSS ASIA K.K.	Japan	Tel: +81-42-778-7251	www.rossasia.co.jp
	AUTOMATIC VALVE INDUSTRIAL LLC	USA	Tel: +1-248-474-6700	www.automaticvalve.com
	ROSS DECCO COMPANY	USA	Tel: +1-248-764-1800	www.rossdecco.com
	ROSS PNEUMATROL Ltd.	United Kingdom	Tel: +44 (0)1254 872277	www.pneumatrol.com
	manufactIS GmbH	Germany	Tel: +49 (0)2013-16843-0	www.manufactis.net

Full-Service Global Locations

There are ROSS Distributors Throughout the World

To meet your requirements across the globe, ROSS distributors are located throughout the world. Through ROSS or its distributors, guidance is available for the selection of ROSS products, both for those using fluid power components for the first time and those designing complex systems.

Other literature is available for engineering, maintenance, and service requirements.

If you need products or specifications not shown in this catalog, please visit ROSS' website, contact ROSS or your ROSS distributor. The ROSS Support Team will be happy to assist you in selecting the best product for your application.

For a current list of countries and local distributors, visit ROSS' at www.rosscontrols.com.