

Thin wall conduit fittings (for EMT conduit)

Straps, clamps, clampbacks/spacers

CLAMPBACKS/SPACERS – MALLEABLE IRON

Applications:

- Provides space between conduit and mounting surface

Standard materials:

- Stamped steel – 1/2" to 1 1/2"
- Malleable iron – 2" to 6"

Standard finish:

- Zinc plated

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
CB1 ^D	1/2"	25	8
CB2 ^D	3/4"	25	10
CB3 ^D	1"	25	12
CB4 ^D	1 1/4"	25	21
CB5 ^D	1 1/2"	25	42
CB6	2"	10	40
CB7	2 1/2"	10	49
CB8	3"	10	62
CB9	3 1/2"	10	91
CB10	4"	10	110
CB11 ^G	5"	5	135
CB12 ^G	6"	5	225

^D Stamped steel.

^G Not UL Listed.

STRAPS – STEEL GALVANIZED

Two hole

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
497 1	1/2"	250	2
497 2	3/4"	150	3
497 3	1"	100	5
497 4	1 1/4"	50	8
497 5	1 1/2"	50	13
497 6	2"	25	14
496 9	2 1/2"	25	19
496 10	3"	25	23
496 11	3 1/2"	25	93
496 12	4"	10	108

CLAMPS – MALLEABLE IRON

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
516 ^G	2 1/2"	5	104
517 ^G	3"	2	120
518 ^G	3 1/2"	2	150
519 ^G	4"	2	220

^G Also for use with rigid/IMC conduit.

CLAMPS – STEEL

Applications:

- To support EMT conduit to mounting surface

Heavy gauge

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
200	1/2"	100	5
201	3/4"	100	6
202	1"	100	6
203	1 1/4"	50	13
204	1 1/2"	25	17
205	2"	25	20
206 ^G	2 1/2"	25	64
207 ^G	3"	25	71
208 ^G	3 1/2"	10	120
209 ^G	4"	10	130

^G Not UL Listed.