



Representative

5346

Catalog Number: Product ID: 7TAD012170R0008 **UPC Number:** 78621005346 **EAN Number:** 05414363075752

Status:

1-1/2 Inch 45 Degree Malleable Iron Insulated Liquidtight Connector

- Ability to install quickly with low torque effort
- To positively bond conduit to box or enclosure.

North American Specifications (UNSPSC)	
UNSPSC	39121420 Liquid tight connectors
IGCC	4585 Liquid tight connectors
Туре	Connectors-45 Degree
Application	Used where flexible metal raceway is installed in
	outdoor or indoor locations where exposed to con-
	tinuous or intermittent moisture.
Standard	UL E23018, CSA
Size	1-1/2 Inch
Material	Malleable Iron
Finish	Electro Zinc Plated/Chromate Coating

European Specifications (ETIM)	
ETIM	EC001180 Screw connection for protective metallic
	hose
Nominal size in inch	1 1/2 inch
Model	45°-elbow
Revolving thread	N
Construction type	External thread
Connection type screw connection to	Thread
housing	
Thread type	NPT
Thread connection size	Other
One-piece	N
Material housing	Other
Approved in combination with protective	Υ
conduit CSA	
Approved in combination with protective	Y
conduit UL	

Packaging	
Inner Quantity	2
Inner Dimensions (inches)	6x4.5x4
Outer Quantity	10
Outer Dimensions (inches)	21.62x6.12x6.62
Weight Uom	121 lbs. per 100

Documents / Support Tools	
Technical Drawing / Data Sheet	TDS000122
Instruction Sheet	TA00210-TB2
Support/Tools	Available on Website
Catalog US	Available on Website

Header	
3D Model	Available on Website



ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com

For further technical assistance, please contact us...

ABB Installation Products Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com